Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-NEXR16



Product Specifications:

Part Number: SCE-NEXR16
Description: Rotary External disconnect 30 To 200 AMP
Height: 34.00"
Width: 17.00"
Depth: 16.00"
Catalog Page: 463
Est. Ship Weight: 63 lbs

Construction

- 0.075 In. carbon steel.
- Seams coninously welded and ground smooth.
- Flange trough collar around all sides of door opening
- Pour in place oil & water resistant gasket
- Collar studs provided for mounting panels.
- Concealed hinge
- Black die cast coinproof/padlocking handle.
- Mounting hardware included.

Application

Designed for use with enclosures that require additional protection against Arc Flash. This enclosure can be used with an environmentally rated enclosure to isolate the main power supply. Increasing personal protection by preventing incidental contact or exposure to the high voltage arc flash and shock hazard, and potentially reducing the PPE level for the lower risk components of the main enclosure.

Finish

ANSI-61 gray powder coating inside and out.

Industry Standards - (IS4)

- NEMA: Type 3R, 4, 12 and Type 13
- UL: Listed Type 3R, 4 and 12
- CSA: Type 3R, 4 and 12
- IEC: IEC 60529
- IP: IP 66

Optional Accessories

SCE-34PX17GALV Galvanized Sub-Plate
SCE-34PXR17GALV Galvannealed Sub-Plate for NEXR
SCE-E115I Interlock, Electrical
SCE-E24I Electrical Interlock 24 VDC
SCE-E460I Electrical Interlock 460 VAC
SCE-NEXDMLK Interlock Kit 30 to 600 Amp (NEXD & NEXR)

Similar Part Numbers

SCE-NEXR12 Rotary External disconnect 30 To 200 AMP
SCE-NEXR18 Rotary External disconnect 30 To 200 AMP
SCE-NEXR24 Rotary External disconnect 30 To 200 AMP

Installation Information

- NextGen External Rotary Disconnect Installation