
Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-PWK2919NF



Product Specifications:

Part Number: SCE-PWK2919NF
Description: Kit, Window
Height: 31.50"
Width: 21.50"
Depth: 0.38"
Catalog Page: 459
Est. Ship Weight: 12 lbs

Application

Designed for use on most SCE Type 1, 3R, 4, 4x, and 12 enclosures. Consist of frame, window, oil-resistant gasketing and mounting hardware. Installed by making a cutout in the enclosure and fastening the window and frame in place. The window is 0.25" UV stable polycarbonate material.
Carbon steel kit powder coated ANSI-61 gray urethane polyester.
Stainless steel kits are made of Type 304 stainless with #4 brushed finish. To maintain a 4x rating, SS must be used.

Industry Standards - (IS24)

- UL: Component Recognized

Notes

Nema Type 1, 3R, 4, 4X & 12

UL Recognized Type 1, 3R & 12
UL File # E69392

Recommend use as Type 3R rating in full outdoor exposure and extreme weather environments.

For more details see Design Considerations When Specifying Your Enclosure on our website.

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

IEC 60529 IP 66

Similar Part Numbers

SCE-PWK1711NF Kit, Window
SCE-PWK1711NFSS Kit, S.S. Window
SCE-PWK2315NF Kit, Window
SCE-PWK2315NFSS Kit, S.S. Window
SCE-PWK2919NFSS Kit, S.S. Window

Installation Information

- NEMA 4 Window Kit