Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-SA39TC



Product Specifications:

Part Number: SCE-SA39TC
Description: Closed Tube Suspension Profile
Height: 39.37"
Width: 2.56"
Depth: 3.54"
Catalog Page: 422
Est. Ship Weight: 12.57 lbs

Construction

- Cast aluminum couplings.
- Extruded aluminum tubes (6060T66).
- Rotating couplings have adjustable tensioner brakes to control movement while in use.
- Rigid, durable bearing in all rotating couplings withstand the stress of continuous use.
- Open or closed tube design.
- Open tube allows for easy access to lay in wiring, with easy to install push fit rubber cover.
- Closed tube acts as conduit for feeding wiring.
- Removable access covers on all couplings with 90 degree turn.
- Hardware and gasket included for installation of coupling to tube.

Application

Designed for use with the SCE HMI enclosures, allows operators to easily move or position an HMI to an ergonomic and comfortable working position. Made of heavy-duty, reliable construction. Suspension Systems can be assembled in a multitude of configurations that allow for machine mount, wall mount, top mount, and floor mount options. Not recommended for enclosure mounted unless adequate reinforcement is added to the Enclosure.

Finish

RAL 7035 powder coated finish.

*Suspension System parts cannot be custom painted

Industry Standards - (IS17)

- NEMA: Not Applicable
- UL: Not Applicable
- CSA: N/A

Notes

Industry Standards
Maintains NEMA 12 and IP 54 enclosure rating with Closed Tube, installed to installation instructions.

Similar Part Numbers

SCE-SA39T Open Tube Suspension Profile

Installation Information

- SA Suspension System
- Suspension System Counter Balance Configurations
- SCE-SAMM

*Suspension System parts cannot be custom painted