Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-VTC5T25B

Product Specifications:

Part Number: SCE-VTC5T25B
Description: Vortex Cooler 500 to 2500 BTU w/Cold Air Dist.
Height: 8.50"
Width: 2.00"
Depth: 2.00"
Catalog Page: 999
Est. Ship Weight: 4 lbs



Construction

- 304 Stainless Steel Body
- Distribution Hose 7 Feet
- Muffler
- 8 SCFM Vortex Generator Installed - 500 BTU (White)
- Included 10 SCFM Vortex Generator - 600 BTU (Orange)
- Included 15 SCFM Vortex Generator - 1000 BTU (Red)
- Included 25 SCFM Vortex Generator - 1800 BTU (Blue)
- Included 35 SCFM Vortex Generator - 2500 BTU (Yellow)

Application

Vortex Cooler with 8 CFM (500BTU) vortex generator installed - 10, 15, 25 and 35 CFM vortex generator included to increase cooling capacity to you needs allowing cooling range of 500 BTU to 2500 BTU with a simple change of the generator. All stainless-steel body with distribution tube and muffler included. Rated for use in temperatures up to 185&degF (85&degC).

Finish

Stainless Steel

Industry Standards - (IS20)

- NEMA: Type 3R, 4, 4X & 12
- UL: Recognized Type 3R, 4, 4X & 12
- IEC: IEC 60529
- IP: IP 56

Notes

To obtain maximum performance from the Vortex Cooler, pressure (psig) and volume (scfm) of air must be maintained. Pressure drops in the compressed air lines should be held at a minimum. Quick connects can starve the Cooler by causing excessive line pressure drops. See Instructions for installation instructions for proper installation.

Optional Accessories

SCE-TEMNO Thermostat (Normally Open)
SCE-FRK120 Kit, Filter/regulator with 120 V Shut off
SCE-FRK24VDC Kit, Filter/regulator with 24VDC Shut off

Installation Information

- Thermal Management Vortex Cooling