# Product data sheet

Specifications



## Manual starter, fractional horsepower, 16A, 2 poles, 1HP at 277VAC, no indicator, NEMA 4 enclosure, 1 conduit opening

2510FW2

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product** | Single Unit Manual Starter |
| **Type** | F |
| **Overload Relay Type** | Melting alloy |

## Complementary

| | |
|---|---|
| **Current Rating** | 16 A |
| **cable entry** | 0.75 NPT (bottom) |
| **Horsepower Rating** | 1 hp 115 V AC<br>1 hp 277 V AC<br>0.75 hp 115 V DC<br>0.75 hp 230 V DC<br>2 hp 230 V AC |
| **Voltage Rating** | 277 V AC<br>230 V DC |
| **Number of Poles** | 2P |
| **Control Unit** | Toggle switch (with lock-off) |
| **Number of Phases** | 1 phase |
| **Pilot Light** | No indicator |
| **Reset** | Manual |
| **Motor starter type** | Non reversing |
| **Electrical Connection** | Screw clamp terminals |
| **Wire Gauge** | 14 AWG...12 AWG copper |
| **Height** | 4.38 in (111.25 mm) |
| **Width** | 3 in (76.2 mm) |
| **Depth** | 4.25 in (107.95 mm) |

## Environment

| | |
|---|---|
| **Product Certifications** | UL listed file E42243 CCN NLRV<br>CSA LR25490 class 3211 05 |
| **NEMA Enclosure Rating** | NEMA 4 die cast zinc alloy standard size |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CP121101 |
| **Discount Schedule** | 0CP1 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **GTIN** | 785901554356 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 3.600 in (9.144 cm) |
| **Package 1 Width** | 4.600 in (11.684 cm) |
| **Package 1 Length** | 5.400 in (13.716 cm) |
| **Package weight(Lbs)** | 2.941 lb(US) (1.334 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **19 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **8 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **0.4 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0.2 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **9 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **2 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **Yes** |
| EU RoHS Directive | **Compliant By Exemption** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |
| PVC free | **Yes** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **74** |
| Circularity Profile | **No need of specific recycling operations** |
| Take-back | **No** |

Image of product / Alternate images

**Alternative**








