Product data sheet

Specifications



Power Relay, Type C, 2 hp, 30A resistive at 300 VAC, SPDT, 1 normally open and 1 normally closed contact, 240 VAC coil

8501CO15V24

Discontinued

Discontinued on: Apr 27, 2026

To be end-of-service on: Dec 31, 2026

Product availability: Stock - Normally stocked in distribution facility

Main

product range	Power Relay 8501C
product type	Power relay
short name	type C
[In] rated line current	30 A
device application	Suited for controlling small single phase motors and other light loads
switch function	SPDT
contact composition	1 NO/1 NC
[Uc] control circuit voltage	240 V AC 50/60 Hz
horsepower rating	2.0 hp
maximum switching voltage	600 V AC

Complementary

class number	8501
phase	1 phase
terminal connects	Screw clamp terminal
wire range	10 AWG copper
terminal tightening torque	11…15 lbf.in (1.2…1.7 N.m)
coil burden	10 VA
mounting	Panel mounting

Environment

ambient temperature range - operational	-22…122 °F (-30…50 °C)
product certifications	UL listed file E78351 CCN NLDX CSA CE
height	2.43 in (61.72 mm)
width	2.5 in (63.5 mm)
depth	2.18 in (55.37 mm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US10CP221131
Discount Schedule	0CP2
GTIN	785901052289
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.200 in (5.588 cm)
Package 1 Width	2.50 in (6.35 cm)
Package 1 Length	2.50 in (6.35 cm)
Package weight(Lbs)	8.320 oz (235.868 g)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations