# Product data sheet

Specifications



## NEMA motor starter, Type S, nonreversing, Size 1, 27A, 10HP at 460VAC, up to 100kA SCCR, 3 phase, 3 pole, Motor Logic, 208VAC coil, NEMA 1 [TAA]

8536SCG3V08H30

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product Type** | Motor starter |
| **Product Range** | S |
| **Starter Type** | Non reversing |

## Complementary

| | |
|---|---|
| **NEMA Size** | 1 |
| **Rated Current** | 27 A |
| **Number of Poles** | 3P |
| **Maximum Voltage Rating** | 600 V AC |
| **Phase** | 3 phase |
| **Type of Overload** | Solid state Motor Logic class 10/20 |
| **Horsepower Rating** | 7.5 HP 200 V AC<br>7.5 HP 230 V AC<br>10 HP 460 V AC<br>10 HP 575 V AC |
| **SCCR** | Circuit-breaker 70 A maximum: 100 kA at 480 V AC<br>Fuse J 60 A maximum: 100 kA at 600 V AC<br>Fuse T 60 A maximum: 100 kA at 600 V AC<br>Fuse RK1 60 A maximum: 100 kA at 600 V AC<br>Fuse RK5 60 A maximum: 100 kA at 600 V AC |
| **Coil Voltage** | 208 V AC 60 Hz |
| **Control Circuit Type** | Common control circuit |
| **Control Units** | No control units |
| **Pilot Light** | Without pilot light |
| **Auxiliary Contacts** | Without |
| **Terminal Type** | Screw clamp terminals |
| **Height** | 10.00 in (254.00 mm) |
| **Width** | 6.00 in (152.40 mm) |
| **Depth** | 5.56 in (141.22 mm) |

## Environment

| | |
|---|---|
| **Enclosure Type** | NEMA 1 painted sheet steel |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Certifications** | UL Listed<br>CSA<br>NEMA |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CP121192 |
| **Discount Schedule** | 0CP1 |
| **GTIN** | 785901771036 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 6.100 in (15.494 cm) |
| **Package 1 Width** | 6.400 in (16.256 cm) |
| **Package 1 Length** | 11.600 in (29.464 cm) |
| **Package weight(Lbs)** | 7.350 lb(US) (3.334 kg) |

## Compliance

| | |
|---|---|
| **Compliance** | TAA Compliant |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **3 556 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **24 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **3 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0.4 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **3 523 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **6 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **Yes** |
| SCIP Number | **04e3cbb1-2155-44d7-bcbd-499999a92721** |
| EU RoHS Directive | **Compliant** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |
| PVC free | **Yes** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **73** |
| Circularity Profile | **No need of specific recycling operations** |
| Take-back | **No** |