# Product data sheet

Specifications



## Push-to-test pilot light, Harmony 9001K, metal, polycarbonate, fresnel, green, 30mm, 24-28V

9001KT35G31

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001K |
| **Product or Component Type** | Push-to-test pilot light |
| **Device short name** | K |

## Complementary

| | |
|---|---|
| **Bezel material** | Metal |
| **Mounting diameter** | 1.2 in (30 mm) |
| **Lens type** | Fresnel plastic |
| **Cap/operator or lens colour** | Green |
| **Bulb base** | BA 9s |
| **Light block supply** | Full voltage 24 V<br>Full voltage 28 V |
| **Shape of screw head** | Round |
| **Light source** | Incandescent bulb |
| **Operating Mode** | Push-to-test |
| **Lens type** | Fresnel |
| **[Us] rated supply voltage** | 24...28 V |
| **Light block supply** | Full voltage |
| **Contacts type and composition** | 1 C/O |
| **Lens material** | Polycarbonate |
| **Size** | 30 mm |

## Environment

| | |
|---|---|
| **Product Certifications** | CE<br>UL listed file E42259 CCN NKCR<br>CSA LR25490 class 3211 03 |
| **NEMA degree of protection** | NEMA 3R/6/13 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS121426 |
| **Discount Schedule** | 0CS1 |
| **GTIN** | 785901036081 |
| **Returnability** | Yes |
| **Country of origin** | MX |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 5.080 in (12.903 cm) |
| **Package 1 Width** | 2.00 in (5.08 cm) |
| **Package 1 Length** | 12.903 in (32.774 cm) |
| **Package weight(Lbs)** | 6.400 oz (181.437 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| SCIP Number | Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d |
| EU RoHS Directive | Compliant By Exemption |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |