# Product data sheet

Specifications



## Push-button head, Harmony 9001SK, plastic, mushroom 35mm, green, 30mm, spring return

9001SKR24G

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001SK |
| **Product or Component Type** | Head for push-button |
| **Device short name** | 9001SK |
| **Operator additional information** | Screw-on plastic with set screw |

## Complementary

| | |
|---|---|
| **Bezel material** | Plastic |
| **Shape of signaling unit head** | Round |
| **Mechanical durability** | 5000000 cycles |
| **Device presentation** | Basic element |
| **Cap/operator or lens colour** | Green |
| **Operator profile** | Mushroom Ø 35 mm |
| **Type of operator** | Spring return |
| **Contacts type and composition** | Without contact block |
| **Size** | 30 mm |

## Environment

| | |
|---|---|
| **Protective treatment** | TC |
| **Ambient Air Temperature for Storage** | -40…158 °F (-40…70 °C) |
| **Ambient Air Temperature for Operation** | -13…158 °F (-25…70 °C) |
| **Overvoltage category** | Class II conforming to IEC 61140 |
| **IP Degree of Protection** | IP65/IP66 |
| **NEMA degree of protection** | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X |
| **Product Certifications** | UL listed file E42259 CCN NKCR<br>CE<br>CSA LR24590 class 3211 03 |
| **Vibration resistance** | 7 gn (f= 2…500 Hz) conforming to IEC 60068-2-6 |

## Ordering and shipping details

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Category** | US10CS121429 |
| **Discount Schedule** | 0CS1 |
| **GTIN** | 785901042174 |
| **Returnability** | No |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 7.620 in (19.355 cm) |
| **Package 1 Width** | 3.00 in (7.62 cm) |
| **Package 1 Length** | 19.355 in (49.161 cm) |
| **Package weight(Lbs)** | 8.000 oz (226.796 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |