Product data sheet

Specifications



To be discontinued

Timing Relay, Type A, pneumatic, off delay, 0.1 to 60 seconds, 15A, 600V, SPDT, timed, 110/120VAC 50/60Hz coil, open

9050AO10DV02

Discontinued on: Mar 31, 2026

End-of-service on: Jun 30, 2026

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product Range	9050A/H
Product Type	Timer
Timing Mode	Off-delay
Timing Range	0.1 s...1 min
Switch Function	SPDT
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Contact Operation	Time delayed 1 NO + 1 NC
current rating	15 A

Complementary

maximum switching voltage	600 V AC
electrical connection	Screw-clamp terminals
reset response time	29 ms - on-delay 27 ms - off-delay
Mounting Support	Panel

Environment

Ambient Temperature Range - Operational	68…104 °F (20…40 °C)
Certifications	UL Listed CSA
Height	2.6 in (67 mm)
Width	4.02 in (102 mm)
Depth	4.4 in (111 mm)

Ordering and shipping details

Category	US10CP121631
Discount Schedule	0CP1
GTIN	785901864110
Returnability	Yes

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.700 in (9.398 cm)
Package 1 Width	4.900 in (12.446 cm)
Package 1 Length	6.600 in (16.764 cm)
Package weight(Lbs)	27.360 oz (775.643 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	50
Package 2 Height	40.0 in (101.6 cm)
Package 2 Width	40.0 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	89.0007 lb(US) (40.37 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No