# Product data sheet

Specifications



## Overload Relay, Type S, melting alloy, separate mount overload, NEMA size 3, 3 pole, 3 phase, 86A, 600VAC

9065SEO12

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | S |
| **Product destination** | Starter |
| **Thermal overload type** | Melting alloy |

## Complementary

| | |
|---|---|
| **NEMA size** | 3 |
| **Number of thermal units required** | 3 |
| **Mounting Support** | Panel |
| **Product or Component Type** | Overload relay |
| **[Ue] rated operational voltage** | 600 V AC |
| **Height** | 5.6 in (142.1 mm) |
| **Width** | 5.3 in (134.9 mm) |
| **Depth** | 5.8 in (146.1 mm) |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CP121661 |
| **Discount Schedule** | 0CP1 |
| **GTIN** | 785901788522 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 6.400 in (16.256 cm) |
| **Package 1 Width** | 6.700 in (17.018 cm) |
| **Package 1 Length** | 8.400 in (21.336 cm) |
| **Package weight(Lbs)** | 3.419 lb(US) (1.551 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **31 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **22 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **1 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0.8 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **5 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **3 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **42** |
| Circularity Profile | **End of Life Information** |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.** |