
Product data sheet

Specifications



Overload Relay, Motor Logic, solid state overload relay, NEMA Size 3, 3 pole, 30A to 90A, 600VAC, separate mount

9065SF320

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Motor Logic
Thermal overload type	Solid state

Complementary

NEMA size	3
Phase	3 phase
Mounting Support	Panel
[Ue] rated operational voltage	600 V AC
Height	5.02 in (127.5 mm)
Width	5.3 in (135.4 mm)
Depth	4.4 in (113 mm)

Ordering and shipping details

Category	US10CP121662
Discount Schedule	0CP1
GTIN	785901751953
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.600 in (14.224 cm)
Package 1 Width	7.100 in (18.034 cm)
Package 1 Length	7.000 in (17.780 cm)
Package weight(Lbs)	2.769 lb(US) (1.256 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	13.000 in (33.020 cm)
Package 2 Width	13.000 in (33.020 cm)
Package 2 Length	16.500 in (41.910 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Weight	12.701 lb(US) (5.761 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**26 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**17 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.7 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**5 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**B65c2eed-aa1c-465f-bca3-a7c8f0610a23**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**42**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**