Product data sheet

Specifications



Power distribution block, Linergy, 3 pole, 2 line, 2 load, 620A Cu, 500A Al, 600V

9080LBA365202

Discontinued on: Sep 2, 2026

Discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9080LB
Product	Power Distribution Block
Current Rating	620 A copper 500 A aluminium

Complementary

Voltage Rating	600 V AC/DC
Mounting Type	Surface mount
Number of poles	3
Terminals per Pole	2 line 2 load
Wire Size	Line 2, 6 AWG...350 kcmil, copper or aluminium Load 2, 6 AWG...350 kcmil, copper or aluminium
Electrical Connection	Tin plated aluminium lugs
SCCR	100 kA UL 508 A
Ambient Air Temperature for Operation	-40…302 °F (-40…150 °C)
Block Material	Phenolic: block
Terminal Tightening Torque	Line lug 275 lbf.in (31.07 N.m) 4 AWG...350 kcmil copper or aluminium Load lug 275 lbf.in (31.07 N.m) 4 AWG...350 kcmil copper or aluminium
Wire stripping length	Line: 1.06 in (26.92 mm) Load: 1.06 in (26.92 mm)
Height	5.5 in (139.7 mm)
Width	8.54 in (216.92 mm)
Depth	3.13 in (79.50 mm)
End Barrier	9080LB53
Net Weight	3.09 lb(US) (1.40 kg)

Environment

Certifications	CE CSA file 70361 class 6228 01 UL recognized E60616 CCN XCFR2

Ordering and shipping details

Category	US1CTR121254

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	CTR1
GTIN	785901097532
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.500 in (8.890 cm)
Package 1 Width	5.900 in (14.986 cm)
Package 1 Length	8.900 in (22.606 cm)
Package weight(Lbs)	3.0005 lb(US) (1.361 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	12.500 in (31.750 cm)
Package 2 Width	9.800 in (24.892 cm)
Package 2 Length	13.300 in (33.782 cm)
Package 2 Weight	19.081 lb(US) (8.655 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**