
# Product data sheet

Specifications




## Operating mechanism, flange mounted, variable depth, 200A, 600V, H, K, J, R fuseholder, switch mechanism

9422TF2

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range** | 9422T |
| **Product** | Disconnect Switch |
| **Disconnect Type** | Fusible disconnect switch |

## Complementary

| | |
|---|---|
| **Mounting Type** | Flange rod variable depth |
| **Current Rating** | 200 A |
| **Horsepower Rating** | 40 hp 200 V AC<br>60 hp 230 V AC<br>125 hp 460 V AC<br>150 hp 575 V AC<br>40 hp 250 V DC |
| **Fuse Rating** | 200 A 250/600 V |
| **Handle Type** | Ordered separately |
| **Fuse Type** | H<br>K<br>J<br>R |

## Environment

| | |
|---|---|
| **Certifications** | CSA<br>UL Recognized |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US1CTR121254 |
| **Discount Schedule** | CTR1 |
| **GTIN** | 785901043744 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 9.200 in (23.368 cm) |
| **Package 1 Width** | 12.100 in (30.734 cm) |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Package 1 Length** | 20.700 in (52.578 cm) |
| **Package weight(Lbs)** | 25.380 lb(US) (11.512 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Use Better

#### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| PVC free | Yes |

### Use Again

#### Repack and remanufacture

| | |
|---|---|
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |