Product data sheet

Specifications



Operating mechanism, flange mounted, variable depth, 400A, 600V, H, K, J, R fuseholder, switch mechanism

9422TG2

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Fusible disconnect switch

Complementary

Mounting Type	Flange rod variable depth
Current Rating	400 A
Horsepower Rating	75 hp 200 V AC 125 hp 230 V AC 250 hp 460 V AC 350 hp 575 V AC 50 hp 250 V DC
Fuse Rating	400 A 250/600 V
Handle Type	Ordered separately
Fuse Type	R K J H

Environment

Certifications	UL Recognized CSA

Ordering and shipping details

Category	US1CTR121254
Discount Schedule	CTR1
GTIN	785901728412
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.00 in (22.86 cm)
Package 1 Width	14.600 in (37.084 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	25.700 in (65.278 cm)
Package weight(Lbs)	67.400 lb(US) (30.572 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	12
Package 2 Height	40.0 in (101.6 cm)
Package 2 Width	40.0 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	809.0002 lb(US) (366.956 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	 **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**