Product data sheet

Specifications



Contactor, Type L, multipole lighting, replacement coil, 110/120VAC 50/60Hz, 8 to 12 poles

9998LH44

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Coil
Accessory / separate part destination	Class 8903 contactor

Complementary

[Ue] rated operational voltage	120 V AC 60 Hz 110 V AC 50 Hz
Inrush power in VA	170 VA 180 VA
Average consumption	35 VA
Height	2.4 in (60.5 mm)
Width	2.1 in (53.6 mm)
Depth	1.5 in (37.1 mm)

Ordering and shipping details

Category	US1CP1021756
Discount Schedule	CP10
GTIN	785901081289
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.200 in (5.588 cm)
Package 1 Width	2.700 in (6.858 cm)
Package 1 Length	3.400 in (8.636 cm)
Package weight(Lbs)	5.760 oz (163.293 g)

Contractual warranty

Warranty (in months)	18

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption

Use Again

Repack and remanufacture

Take-back	No