Product data sheet

Specifications



Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts

AP9613

Discontinued

Discontinued on: Nov 7, 2025

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Presentation	UPS management SmartSlot Card with Dry Contact (relay) support to monitor external triggers and initiate actions on external devices.

Main

Product or Component Type	Dry contact
Number of rack unit	0U
Provided Equipment	User Manual USB cable
Range of Product	Management Options and Cables

Physical

Color	Black
Height	1.5 in (3.8 cm)
Width	4.8 in (12.1 cm)
Depth	4.5 in (11.4 cm)
Net Weight	0.46 lb(US) (0.21 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Conformance

Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6 FCC Part 15 class A

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Relative Humidity	0…95 %
Operating altitude	0...10000 ft

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	5…149 °F (-15…65 °C)
Storage Relative Humidity	0…95 %
Storage altitude	0…50000 ft (0…15240 m)

Ordering and shipping details

Category	09305 - INDUSTRIAL UPS
GTIN	731304293842
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.850 in (4.700 cm)
Package 1 Width	6.496 in (16.500 cm)
Package 1 Length	9.213 in (23.400 cm)
Package weight(Lbs)	14.109 oz (400.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	7.013 lb(US) (3.181 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**282 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**4 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**278 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**1cdb2fed-a06f-4574-913d-8df8e70936b2**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
Halogen content performance	**Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**