Product data sheet

Specifications



APC NetShelter SX, Server Rack Enclosure, 42U, Black, 1991H x 600W x 1070D mm [TAA]

AR3100

Discontinued

Main

Product or Component Type	Rack enclosure
Number of rack unit	42U
Rack Width	19"
Permanent permissible load	2250 lb(US) (1020.6 kg) dynamic 3750 lb(US) (1701.0 kg) static
Provided equipment	Baying hardware Key(s) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters Side Panels

Complementary

Mounting Mode	Not rack-mountable
Minimum Mounting Depth	7.5 in (190.5 mm)
Maximum Mounting Depth	36.02 in (914.9 mm)
Color	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Height	78.4 in (1991 mm)
Width	23.6 in (600 mm)
Depth	42.1 in (1070 mm)
Net Weight	275.78 lb(US) (125.09 kg)

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304226390
Returnability	No

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	29.606 in (75.200 cm)
Package 1 Width	45.512 in (115.600 cm)
Package 1 Length	83.386 in (211.800 cm)
Package weight(Lbs)	318.678 lb(US) (144.550 kg)

Compliance

Compliance	TAA Compliant BAA Compliant via COTS

Contractual warranty

Warranty (in months)	60

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**439 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**419 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**11 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**9 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative






35
34
33
32
31
30




APC


35
34
33
32
31


35
34
33
32
31
30















