Product data sheet

Specifications



discrete input module, Modicon X80, 32 inputs, 24V DC positive

BMXDDI3202K

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon X80
Product or Component Type	Discrete input module
Discrete input number	32
Discrete input voltage	24 V DCisolated
Discrete input logic	Positive logic (sink)

Complementary

Discrete input number	32 isolated conforming to IEC 60947-5-2 at 24 V DC 32 isolated conforming to IEC 61131-2 type 3 at 24 V DC
Input wiring mode	2 or 3 wires
Discrete input current	2.5 mA at 24 V DC
Voltage state 1 guaranteed	>= 11 V
Voltage state 0 guaranteed	< 5 V
Current state 1 guaranteed	>= 2 mA
Current state 0 guaranteed	<= 0.5 mA
Input impedance	9600 Ohm
Paralleling of inputs	No
Insulation resistance	> 10 MOhm 500 V DC
DC typical response time	4 ms
DC maximum response time	7 ms
Sensor power supply	19…30 V
Typical current consumption	121 mA DC
Current consumption	160 mA 3.3 V DC
Power dissipation in W	3.9 W
Isolation between channels and bus	1500 V for 1 minute
Hot swapping fallback	Yes
MTBF reliability	905000 H
Voltage detection threshold	< 14 V DC sensor fault > 18 V DC sensor OK
Local signalling	1 LED (green) for module operating (RUN) 1 LED per channel (green) for channel diagnostic 1 LED (red) for module error (ERR) 1 LED (red) for module I/O
Height	5.3 in (134.6 mm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	1.3 in (32 mm)
Depth	3.4 in (86 mm)
Net Weight	0.247 lb(US) (0.112 kg)

Environment

IP Degree of Protection	IP20
Protective treatment	Standard version
Marking	CE UKCA CULus RCM EAC
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Dielectric strength	1500 V AC 50/60 Hz 1 minute, primary/secondary 500 V DC 1 minute, between group of channels
Ambient air temperature for operation	32…140 °F (0…60 °C)
Ambient air temperature for storage	-40…185 °F (-40…85 °C)
Relative humidity	5…95 % 131 °F (55 °C) without condensation
Operating altitude	0...6561.68 ft (0...2000 m) 2000...5000 m with derating
Pollution degree	2
Vibration resistance	3 gn
Shock resistance	30 gn

Ordering and shipping details

Category	US1PC3418160
Discount Schedule	PC34
GTIN	3595863910018
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.047 in (5.200 cm)
Package 1 Width	4.331 in (11.000 cm)
Package 1 Length	4.528 in (11.500 cm)
Package weight(Lbs)	5.044 oz (143.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	6.305 lb(US) (2.860 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**41 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**20 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**21 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.3 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**Ff2a0a17-800d-4c82-9983-c10cf1a6b7a2**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again


Repack and remanufacture

Recyclability potential, in %	**3**
Circularity Profile	**End of Life Information**
Take-back	**No**

Dimensions Drawings

Modules Mounted on Racks

Dimensions




(1) With removable terminal block (cage, screw or spring).
(2) With FCN connector.
(3) On AM1 ED rail: 35 mm wide, 15 mm deep. Only possible with BMXXBP0400/0400H/0600/0600H/0800/0800H rack.

Rack references	a in mm	a in in.
BMXXBP0400 and BMXXBP0400H	242.4	09.54
BMXXBP0600 and BMXXBP0600H	307.6	12.11
BMXXBP0800 and BMXXBP0800H	372.8	14.68
BMXXBP1200 and BMXXBP1200H	503.2	19.81


Connections and Schema

Connecting the Module

Input Circuit Diagram



Module Connection



(1) fuse: fast blow fuse of 0.5 A for each 16-channel group


power supply 24 VDC
SPS sensor power supply

Image of product / Alternate images

Alternative






SN:XXXXXXXXXXX
PV:XX
RL:XX




Schneider
Electric
Modicon
BMXDDI3202K
DIG 32I 24 VDC SINK
DOM : XXXX

