Product data sheet

Specifications



Control relay, TeSys SK, 1NO+1NC, <= 690V, 24V DC standard coil

CA3SK11BD

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product name	TeSys CASK
Product or Component Type	Control relay
Device short name	CA3SK
Contactor application	Control circuit
Utilisation category	DC-13 AC-15
Pole contact composition	1 NO + 1 NC
[Ue] rated operational voltage	<= 690 V <= 400 Hz
Control circuit type	DC standard
[Uc] control circuit voltage	24 V DC

Complementary

[Ith] conventional free air thermal current	10 A (at 131 °F (55 °C))
Associated fuse rating	10 A gL conforming to VDE 0660 10 A gL conforming to IEC 60947
[Ui] rated insulation voltage	690 V IEC 60947 690 V VDE 0110 group C 690 V BS 5424 690 V UL 508 690 V CSA C22.2 No 14
Mounting Support	Rail Plate
Connections - terminals	screw clamp terminals 1 0.002…0.009 in² (1.5…6 mm²)solid screw clamp terminals 2 0.002…0.006 in² (1.5…4 mm²)solid screw clamp terminals 1 0.0008…0.009 in² (0.5…6 mm²)flexible without cable end screw clamp terminals 1 0.0005…0.009 in² (0.35…6 mm²)flexible with cable end screw clamp terminals 2 0.0005…0.002 in² (0.35…1.5 mm²)flexible with cable end screw clamp terminals 2 0.0005…0.004 in² (0.35…2.5 mm²)flexible without cable end
Tightening torque	7.08 lbf.in (0.8 N.m) screw clamp terminals pozidriv No 1
Control circuit voltage limits	Operational: 0.85...1.1 Uc (at <122 °F (50 °C)) Drop-out: 0.1...0.75 Uc (at <122 °F (50 °C))
Operating time	4...6 ms coil de-energisation and NO opening 8...12 ms coil energisation and NO closing 6...8 ms coil de-energisation and NC closing 10...18 ms coil energisation and NC opening
Mechanical durability	10 Mcycles
Maximum operating rate	1200 cyc/h
Inrush power in W	2.2 W 68 °F (20 °C))

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Hold-in power consumption in W	2.2 W 68 °F (20 °C)
Heat dissipation	2.2 W
Height	2.2 in (56 mm)
Width	1.06 in (27 mm)
Depth	2.2 in (55.5 mm)
Net Weight	0.291 lb(US) (0.132 kg)

Environment

Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1
Product Certifications	CB Scheme cULus EAC CE UKCA
IP degree of protection	IP2X
Protective treatment	TC IEC 60068
Ambient Air Temperature for Operation	-4…122 °F (-20…50 °C)
Ambient Air Temperature for Storage	-58…158 °F (-50…70 °C)
Operating altitude	6561.68 ft (2000 m) without derating

Ordering and shipping details

Category	US1CTR121253
Discount Schedule	CTR1
GTIN	3389110564235
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.4 in (3.5 cm)
Package 1 Width	2.4 in (6.0 cm)
Package 1 Length	2.6 in (6.5 cm)
Package weight(Lbs)	4.4 oz (124.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	40
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	5.9 in (15.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	11.424 lb(US) (5.182 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**58 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.6 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**57 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**Bf876e8d-5be9-45ba-9d97-ac1c3aec5384**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**

Use Again

Repack and remanufacture

Recyclability potential, in %	**63**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**