Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 1 NO, early break, front mounting, for GS2 with front/side handle

GS1AM110

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	TeSys
Device short name	GS1AM
Product or Component Type	Auxiliary contact
Contact application	O, I and test position signalling
Range compatibility	TeSys TeSys GS fuse-switch disconnector FuPact FuPacT GS fuse-switch disconnector
Contacts type and composition	1 NO
Contact operation	Early-break
[Ith] conventional free air thermal current	10 A (at 104 °F (40 °C))
[Ie] rated operational current	6 A 120 V AC-15 3 A 240 V AC-15 1.8 A 400 V AC-15 1.5 A 480 V AC-15 2.8 A 24 V DC-13 1.4 A 48 V DC-13 0.55 A 125 V DC-13 0.27 A 250 V DC-13 0.15 A 400 V DC-13

Complementary

Mechanical durability	5 Mcycles
Electrical durability	1 Mcycles AC-15
switch rated current	30 A 32 A 50 A 60 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A 600 A 630 A 800 A 1250 A
Fuse type	NFC DIN BS CC J
Type of operating handle	External frontal External right side External left side

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting Location	Front face
Net Weight	0.033 lb(US) (0.015 kg)

Ordering and shipping details

Category	US1CTR121254
Discount Schedule	CTR1
GTIN	3389110181760
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.5 in (9 cm)
Package 1 Width	3.1 in (8 cm)
Package 1 Length	0.8 in (2 cm)
Package weight(Lbs)	0.5 oz (13 g)
Unit Type of Package 2	S01
Number of Units in Package 2	40
Package 2 Height	5.9 in (15 cm)
Package 2 Width	5.9 in (15 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	24.9 oz (707 g)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**