Product data sheet

Specifications



rear panel, Harmony STO & STU, module, dark grey, width 118mm, depth 40.1mm

HMIS5T

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony STU
Product or Component Type	Rear panel

Complementary

Enclosure Material	PC/PBT
Height	3.86 in (98.15 mm)
Width	4.6 in (118 mm)
Depth	1.6 in (40.1 mm)
Net Weight	0.780 lb(US) (0.354 kg)

Environment

Product Certifications	UKCA UKEX

Ordering and shipping details

Category	US10MC222569
Discount Schedule	0MC2
GTIN	3595864155074
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.04 in (12.8 cm)
Package 1 Width	2.09 in (5.3 cm)
Package 1 Length	7.2 in (18.3 cm)
Package weight(Lbs)	12.8 oz (363.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Weight	13.902 lb(US) (6.306 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	384
Package 3 Height	31.5 in (80.0 cm)
Package 3 Width	47.2 in (120.0 cm)
Package 3 Length	43.3 in (110.0 cm)
Package 3 Weight	353.498 lb(US) (160.344 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**143 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**35 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**108 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

F-gas usage performance	**Only air and vacuum used for insulation / breaking, no F-gas including SF6**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**3d02a16a-b371-402f-abda-886a20922dcb**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
Halogen content performance	**Product contains halogen above thresholds**
PVC free	**No**
Silicon free	**No**

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	**User replaceable**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative






HMIS5T
DC24V 5.2W Class 2
PV 07 RL-05 SV5.0
IEC 61131-2
Made in China
DANGER
USB2
USB1
ETH
CAN
RS485
PWR 24V




HMIS5T