# Product data sheet

Specifications



## Load center, Homeline, 1 phase, 12 spaces, 24 circuits, 125A convertible main lugs, PoN, NEMA1, gnd bar, combo cover

HOM1224L125PGC

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product Type** | Load Center |
| **Marketing Trade Name** | Homeline |
| **Load Center Type** | PoN Convertible Mains (lugs) |
| **Rated Current** | 125 A |
| **Number of Spaces** | 12 |
| **Maximum Number of Single Pole Circuits** | 24 |
| **Enclosure Rating** | NEMA 1 indoor enclosure |
| **Cover Type** | Combination flush/surface cover |
| **Electrical Connection** | Lugs |
| **Provided Equipment** | Grounding bar 1) |

## Complementary

| | |
|---|---|
| **Max Short Circuit Current Rating** | 10 kA |
| **Maximum Number of Tandem Breakers** | 12 |
| **Number of Phases** | 1 phase 3 wires |
| **Voltage Rating** | 120/240 V AC |
| **Wire Size** | 6 AWG...2/0 AWG aluminium<br>6 AWG...1 AWG copper |
| **Busbar Material** | Tin plated aluminium: busbar |
| **Enclosure Material** | Welded sheet steel |
| **Surface Finish** | Baked enamel Gray |
| **Box Number** | 6 |
| **Bus Rated Current** | 125.0 A |
| **Height** | 17.9 in (455 mm) |
| **Width** | 14.3 in (362 mm) |
| **Depth** | 3.7 in (95 mm) |

## Environment

| | |
|---|---|
| **Ambient Air Temperature for Operation** | 23 °F (-5 °C)<br>104 °F (40 °C) |
| **Product Certifications** | UL listed file E-6294 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Ordering and shipping details

| | |
|---|---|
| **Category** | US1DE3C00045 |
| **Discount Schedule** | DE3C |
| **GTIN** | 785901864776 |
| **Returnability** | Yes |
| **Country of origin** | US |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 5.800 in (14.732 cm) |
| **Package 1 Width** | 16.100 in (40.894 cm) |
| **Package 1 Length** | 20.700 in (52.578 cm) |
| **Package weight(Lbs)** | 18.541 lb(US) (8.410 kg) |
| **Unit Type of Package 2** | PAL |
| **Number of Units in Package 2** | 42 |
| **Package 2 Height** | 42.800 in (108.712 cm) |
| **Package 2 Width** | 42.000 in (106.680 cm) |
| **Package 2 Length** | 48.000 in (121.920 cm) |
| **Package 2 Weight** | 809.0002 lb(US) (366.956 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **43 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **40 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **3 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **0.1 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **0.7 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | **Compliant** |
| REACh Regulation | **Free of Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **89** |
| Circularity Profile | **No need of specific recycling operations** |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.** |

Image of product / Alternate images

**Alternative**




