Product data sheet

Specifications



Mini circuit breaker, Homeline, 100A, 2 pole, 120/240VAC, 10kA AIR, standard type, plug in, UL

HOM2100

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	100 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Screw clamp terminals
Wire Size	1 x 4 AWG...2/0 AWG (aluminium/copper)

Complementary

Tightening torque	42.5 lbf.in (4.8 N.m) 0.006…0.08 in² (4…50 mm²) (4 AWG...2/0 kcmil)
Height	3.13 in (79.50 mm)
Width	2 in (50.8 mm)
Depth	2.98 in (75.69 mm)
Net Weight	0.948 lb(US) (0.430 kg)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)

Ordering and shipping details

Category	US1DE3D00146
Discount Schedule	DE3D
GTIN	785901065753
Returnability	Yes
Country of origin	MX

Packing Units

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.400 in (8.636 cm)
Package 1 Width	2.300 in (5.842 cm)
Package 1 Length	3.800 in (9.652 cm)
Package weight(Lbs)	15.200 oz (430.913 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	36
Package 2 Height	3.800 in (9.652 cm)
Package 2 Width	14.00 in (35.56 cm)
Package 2 Length	20.800 in (52.832 cm)
Package 2 Weight	31.449 lb(US) (14.265 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	1728
Package 3 Height	40.0 in (101.6 cm)
Package 3 Width	40.0 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)
Package 3 Weight	1486.999 lb(US) (674.491 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**12 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**3 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.3 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**9 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.4 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**30**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative






Homeline™
HOM2100C
100A
120/240 VAC ~ 50/60 Hz
10,000 AIR/A nom.I
2 Poles
Polos
Market-leading
circuit protection
#1
Qwik-Open™
technology -
Overload and Short
circuit protection


HOM2100
1730
Assembled in MX
with MX &
Foreign Parts
62


INTERRUPTING
RATING
10 000 A
50/60 Hz
A nom. HAIR
002
04
40°C






INTERRUPTING
RATING
10 000 A
40°C


HOM2100
1730
Assembled in MX
with MX &
Foreign Parts