Product data sheet

Specifications



Handles and front plates, TeSys Control, red handle, yellow front, 1-3 padlocking, 4 screws fixing, for V5/ V6

KCF3PZ

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Device short name	KCF3
Product or Component Type	Rotary handle
Product Compatibility	V5 V6
Handle colour	Red

Complementary

Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 0.2…0.3 in (4…8 mm)
Marking	0 - 1
Fixing mode	By 4 screws
handle front plate dimension	90 x 90 mm
Height	3.5 in (90 mm)
Width	3.5 in (90 mm)
Net Weight	0.35 lb(US) (0.16 kg)

Environment

IP degree of protection	IP65

Ordering and shipping details

Category	US1CTR121254
Discount Schedule	CTR1
GTIN	3389110804775
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.937 in (10.000 cm)
Package 1 Width	5.984 in (15.200 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	3.740 in (9.500 cm)
Package weight(Lbs)	6.772 oz (192.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	5.313 lb(US) (2.410 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	80
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	66.128 lb(US) (29.995 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**30 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**29 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.4 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**

Use Again

Repack and remanufacture

Recyclability potential, in %	**57**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**