Product data sheet

Specifications



Enclosed DOL starter, TeSys LE, 4kW at 400V, Ith: 9A, 230V AC coil, including 1 LC1D, 2 push-buttons

LE1D09P7

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys
Product name	TeSys LE
Product or Component Type	Enclosed DOL starter
Device short name	LE1D
Device Application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay ordered separately Contactor
Control type	Push-button start Green I Push-button stop/reset Red O
Motor power kW	4 kW 380/400 V AC 50/60 Hz 4 kW 415 V AC 50/60 Hz 4 kW 440 V AC 50/60 Hz 2.2 kW 220/230 V AC 50/60 Hz 5.5 kW 500 V AC 50/60 Hz 5.5 kW 660/690 V AC 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz

Complementary

[Ithe] conventional enclosed thermal current	9 A
Cable entry number	2 ISO20 top 2 ISO20 bottom
Width	3.5 in (88 mm)
Height	6.5 in (166 mm)
Depth	5.06 in (128.5 mm)
Net Weight	2.03 lb(US) (0.92 kg)

Environment

Standards	IEC 60947-4-1 UL 60947-4-1
Product Certifications	CB Scheme UL CE UKCA
IP degree of protection	IP65 IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Ambient air temperature for operation	23…104 °F (-5…40 °C)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	Polycarbonate
Environmental characteristic	Standard environment

Ordering and shipping details

Category	US1CTR421258
Discount Schedule	CTR4
GTIN	3389110541243
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.890 in (17.500 cm)
Package 1 Width	5.906 in (15.000 cm)
Package 1 Length	8.268 in (21.000 cm)
Package weight(Lbs)	30.829 oz (874.000 g)
Unit Type of Package 2	P06
Number of Units in Package 2	30
Package 2 Height	29.528 in (75.000 cm)
Package 2 Width	23.622 in (60.000 cm)
Package 2 Length	31.496 in (80.000 cm)
Package 2 Weight	87.391 lb(US) (39.640 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**107 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**9 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**95 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**9f35ee05-3751-48fa-a30a-96c8b2cda02b**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**

Use Again

Repack and remanufacture

Recyclability potential, in %	**37**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**