Product data sheet

Specifications



outlet grille plast cut out 125x125mm ext dim 137x117mm IP54

NSYCAG125LPF

Product availability: Stock - Normally stocked in distribution facility

Main

Range	ClimaSys
Product	ClimaSys CA
Range compatibility	ClimaSys ClimaSys CV fan
Certification	CSA
Product or Component Type	Outlet grille
Accessory / separate part category	Thermal management accessory
Accessory / separate part destination	ClimaSys ventilation system
Fixing Mode	Clipped By screws
Device composition	1 support frame 1 external part 1 G2 M1 synthetic standard filter

Complementary

Material	Injected thermoplastic (ASA PC)
color	External part Gray RAL 7035)
Cut-out dimensions	125 x 125 mm
Height	External: 6.7 in (170 mm)
Width	External: 5.9 in (150 mm)
Depth	External : 0.6 in (15 mm)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480151538
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.772 in (4.500 cm)
Package 1 Width	6.102 in (15.500 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	7.087 in (18.000 cm)
Package weight(Lbs)	7.760 oz (220.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	56
Package 2 Height	15.157 in (38.500 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	28.660 lb(US) (13.000 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	448
Package 3 Height	35.827 in (91.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	262.350 lb(US) (119.000 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**2 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.4 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
PVC free	**Yes**
Silicon free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**8**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**