
Product data sheet

Specifications



Terminal block, Linergy TR, spring type, feed through, 4 points, 2.5mm², grey, set of 50

NSYTRR24

Discontinued on: Aug 27, 2026

Discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Linergy
Product name	Linergy TR
Product or Component Type	Terminal block
Device short name	TRR
Accessory / separate part category	Connection accessory
Terminal block type	Passthrough
Terminal block level	1
Mounting Mode	Clip-on
Nominal cross section	0.004 in² (2.5 mm²)
Length	2.8 in (72 mm)
color	Gray
Quantity per Set	Set of 50

Complementary

Width	0.2 in (5.2 mm)
Height	1.4 in (36.5 mm)
Connections - terminals	2 x spring terminal downstream 2 x spring terminal upstream
number of connections	4
Connection position	Top
Number of measurement input	2
Cable cross section	0.0001…0.004 in² (0.08…2.5 mm²), flexible without cable end 0.0001…0.006 in² (0.08…4 mm²), solid with cable end 0.0003…0.004 in² (0.2…2.5 mm²), flexible with cable end 0.0001…0.006 in² (0.08…4 mm²), solid without cable end
Wire stripping length	0.4 in (10 mm)
Tool type	Connection flat screwdriver Disconnection flat screwdriver
[Ue] rated operational voltage	600 V CSA 800 V EN/IEC 60947-7-1 600 V UL
Line Rated Current	20 A CSA 20 A UL 24 A EN/IEC 60947-7-1

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	Polyamide 6/6: insulating case Copper alloy: connector and screw Copper alloy: commoning link Chromium-nickel steel: spring
Dielectric loss	0.01 at 1 MHz IEC 60250 0.01 at 1 MHz VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m IEC 60093 10000 MΩ.m VDE 0303-T30
Surface resistance	1000 GΩ IEC 60093 1000 GΩ VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) IEC 60093 500 CTI (> 400 kB) VDE 0303-T30
Flame retardance	V0 0.03 in (0.8 mm) UL 94
Net Weight	0.3 oz (8.5 g)
Range compatibility	PrismaSeT G PrismaSeT P PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
Product Compatibility	Spacial enclosures

Environment

Product Certifications	CSA UL DNV GL VDE
Dielectric strength	1000 V IEC 60243-1
Ambient air temperature for operation	-40…266 °F (-40…130 °C) IEC 60216-1 -40…266 °F (-40…130 °C) VDE 0304-T21

Ordering and shipping details

Category	US1CTR121254
Discount Schedule	CTR1
GTIN	3606480532580
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.197 in (0.500 cm)
Package 1 Width	1.378 in (3.500 cm)
Package 1 Length	2.874 in (7.300 cm)
Package weight(Lbs)	0.317 oz (9.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	50

Package 2 Height	1.772 in (4.500 cm)
Package 2 Width	3.543 in (9.000 cm)
Package 2 Length	10.827 in (27.500 cm)
Package 2 Weight	17.143 oz (486.000 g)
Unit Type of Package 3	P06
Number of Units in Package 3	8400
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	213.055 lb(US) (96.640 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**5 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**4 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen content performance	**Halogen free plastic parts product**
PVC free	**Yes**
Silicon free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**37**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**