
Product data sheet

Specifications



Terminal block, Linergy TR, green, 4mm2, passthrough, 2 points, set of 10

NSYTRV42GN

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Linergy
Product name	Linergy TR
Product or Component Type	Terminal block
Device short name	TRV
Accessory / separate part category	Connection accessory
Terminal block type	Passthrough
Terminal block level	1
Mounting Mode	Clip-on
Nominal cross section	0.006 in² (4 mm²)
Length	1.9 in (47.7 mm)
color	Green
Quantity per Set	Set of 50

Complementary

Width	0.2 in (6.2 mm)
Height	1.9 in (47.5 mm)
Connections - terminals	1 x screw terminal upstream M3) 1 x screw terminal downstream M3)
number of connections	2
Connection position	Sideways
Number of measurement input	2
Cable cross section	0.0002…0.009 in² (0.14…6 mm²), solid with cable end 0.0003…0.006 in² (0.2…4 mm²), flexible with cable end 0.0003…0.009 in² (0.2…6 mm²), solid without cable end 0.0003…0.009 in² (0.2…6 mm²), flexible without cable end
Tightening torque	5.3…7.08 lbf.in (0.6…0.8 N.m)
Wire stripping length	0.4 in (9 mm)
Tool type	Connection screwdriver Disconnection screwdriver
[Ue] rated operational voltage	1000 V EN/IEC 60947-7-1 600 V CSA 600 V UL
Line Rated Current	32 A EN/IEC 60947-7-1 30 A CSA 30 A UL

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	Polyamide 6/6: insulating case Copper alloy: connector and screw Copper alloy: commoning link Chromium-nickel steel: spring
Dielectric loss	0.01 at 1 MHz IEC 60250 0.01 at 1 MHz VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m IEC 60093 10000 MΩ.m VDE 0303-T30
Surface resistance	1000 GΩ IEC 60093 1000 GΩ VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) IEC 60093 500 CTI (> 400 kB) VDE 0303-T30
Flame retardance	V0 0.03 in (0.8 mm) UL 94
Net Weight	0.3 oz (9.4 g)
Range compatibility	PrismaSeT G PrismaSeT P PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
Product Compatibility	Spacial enclosures

Environment

Product Certifications	DNV CSA UL VDE GL
Dielectric strength	1000 V IEC 60243-1
Ambient air temperature for operation	-40…266 °F (-40…130 °C) IEC 60216-1 -40…266 °F (-40…130 °C) VDE 0304-T21

Ordering and shipping details

Category	US1CTR121254
Discount Schedule	CTR1
GTIN	3606480531927
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.236 in (0.600 cm)
Package 1 Width	1.850 in (4.700 cm)
Package 1 Length	1.850 in (4.700 cm)
Package weight(Lbs)	0.317 oz (9.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	50

Package 2 Height	1.969 in (5.000 cm)
Package 2 Width	2.362 in (6.000 cm)
Package 2 Length	12.520 in (31.800 cm)
Package 2 Weight	16.825 oz (477.000 g)
Unit Type of Package 3	S03
Number of Units in Package 3	1150
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	25.309 lb(US) (11.480 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**6 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**6 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**8e5413ff-f1a1-4909-ad03-977097e33bd2**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
Halogen content performance	**Halogen free plastic parts product**
PVC free	**Yes**
Silicon free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**46**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**