Product data sheet

Specifications



Enclosed molded case switch, QO, 60A, 2 pole, 240VAC, 22kA, air conditioning, NEMA 3R, nonmetal

QO200TRNM

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Enclosed molded case switch Weatherproof enclosure
Range of Product	QO

Complementary

Current Rating	60 A
Interrupt Rating	22 kA
Number of Phases	1 phase
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker QO 2P
For Use With	air conditioner
Product Certifications	UL Listed
Indoor/Outdoor Use	Enclosed outdoor
Voltage Rating	240 V AC
Ambient Air Temperature for Operation	104 °F (40 °C)
Height	8.7 in (222 mm)
Width	6.5 in (165 mm)
Depth	3.9 in (99 mm)
Product Weight	1.900 lb(US) (0.862 kg)

Ordering and shipping details

Category	US1DE2A00044
Discount Schedule	DE2A
GTIN	785901328018
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.300 in (10.922 cm)
Package 1 Width	6.800 in (17.272 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	10.200 in (25.908 cm)
Package weight(Lbs)	33.919 oz (961.615 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	11.200 in (28.448 cm)
Package 2 Width	14.300 in (36.322 cm)
Package 2 Length	21.900 in (55.626 cm)
Package 2 Weight	22.300 lb(US) (10.115 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	200
Package 3 Height	47.000 in (119.380 cm)
Package 3 Width	40.000 in (101.600 cm)
Package 3 Length	48.000 in (121.920 cm)
Package 3 Weight	459.999 lb(US) (208.652 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**7 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**6 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.3 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0.1 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Recyclability potential, in %	**88**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative

