Product data sheet

Specifications



Tandem mini circuit breaker, QO, 1 x 1 pole at 20A, 1 x 1 pole at 30A, 120/240VAC, 10kA, plug in

QO2030

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	30 A 20 A
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Tandem
Ratings	HACR rated
Electrical Connection	Pressure plate
Type of Packing	Box

Complementary

Interrupt Rating	10 kA 120/240 V AC
Number of Panel Spaces	1
Wire Size	14 AWG...8 AWG copper or aluminium
Tightening Torque	24.8 lbf.in (2.8 N.m)
Height	3.2 in (82 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Net Weight	0.331 lb(US) (0.150 kg)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A00181
Discount Schedule	DE2A
GTIN	785901001010
Returnability	Yes
Country of origin	MX

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.800 in (2.032 cm)
Package 1 Width	3.500 in (8.890 cm)
Package 1 Length	3.500 in (8.890 cm)
Package weight(Lbs)	5.280 oz (149.685 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	3600
Package 2 Height	40.000 in (101.600 cm)
Package 2 Width	40.000 in (101.600 cm)
Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	1187.999 lb(US) (538.867 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**4 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**3 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**Yes**
SCIP Number	**Af42fb01-813d-40c0-ae28-b8b3299dbc99**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**
Halogen content performance	**Halogen free product**

Use Again

Repack and remanufacture

Recyclability potential, in %	**32**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative




If installed in USA: For replacement use
only, not CTL (Circuit Limiting) assemblies.
Si se va a instalar en los Estados Unidos:
utilícelo solamente como repuesto, no
como ensambles del interruptor automático
limitador.
Si installé aux E.U.: utilisé comme appareil
de rechange seulement, pas comme
protection des assemblages de circuits de
limitation.

