Product data sheet

Specifications



Discontinued

Enclosed circuit breaker, QO, 200A, 2 pole, 120/240VAC, 22kA, bolt on mount, NEMA 3R

QOM2E2200NRB

Discontinued on: Jul 24, 2026

End-of-service on: Jan 16, 2026

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Enclosed circuit breaker
Range of Product	QO
Load Center Type	Main breaker
Frame Size	QOM2

Complementary

Current Rating	200 A
Interrupt Rating	22 kA 120/240 V AC 50/60 Hz
Number of Poles	2P
Number of Phases	1 phase
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker QOM2
Product Certifications	UL Listed
Mounting mode	Bolt-on
Electrical Connection	Lugs
Wire Size	4 AWG...300 kcmil aluminium/copper
Indoor/Outdoor Use	Outdoor
Voltage Rating	120/240 V AC
Ambient Air Temperature for Operation	104 °F (40 °C)
Tightening Torque	6 N.m, 12 AWG...2/0 AWG
Cable cross section	0.006…0.1 in² (4…65 mm²) - 12 AWG...2/0 AWG
Height	24.6 in (624 mm)
Width	8.7 in (220 mm)
Depth	4.09 in (104 mm)
Product Weight	16.250 lb(US) (7.371 kg)

Ordering and shipping details

Category	US1DE3A00100
Discount Schedule	DE3A

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	785901375302
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.200 in (15.748 cm)
Package 1 Width	9.500 in (24.130 cm)
Package 1 Length	25.300 in (64.262 cm)
Package weight(Lbs)	16.250 lb(US) (7.371 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**57 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**53 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0.1 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.8 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
OECD PFAS Regulation	**No OECD PFAS Chemicals Present**
POP Directive	**No POPs**
Halogen content performance	**Halogen free plastic parts product**
PVC free	**Yes**

Use Again

Repack and remanufacture

Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative

