Product data sheet

Specifications



Cover Plate for Sensor Base for SmartX IP Controllers Color Touchscreen with Occupancy Sensor - Sensor Base not included

SXWSCDPSELXX

Product availability: Stock - Normally stocked in distribution facility

Main

Range	SpaceLogic
Product or Component Type	Cover
Product name	SmartX Living Space Sensor
Device Application	HVAC Temperature control Fan speed controller
Product certifications	CE conforming to EN 61000-6-3 RCM EAC ICES-003
Display Resolution	320 x 240 pixels
Display size	2.4 inch
Display Type	Colour touchscreen
Flame Retardance	UL94-V0
IP Degree of Protection	IP20
Location	Living Space
Depth	0.8 in (20 mm)
Height	4.5 in (115 mm)
Width	3.3 in (85 mm)
Ambient Air Temperature for Operation	32…122 °F (0…50 °C)
Standards	UL 916 FCC Part 15 class B
Color	White
Sensor Type	PIR
[Us] Rated Supply Voltage	24 V DC
Device presentation	Cover plate
Surface Finish	Matte

Complementary

Control type	tactile
Material	ABS (acrylonitrile butadiene-styrene) GF10 FR
Function Available	Override switches Setpoint adjustment Blind control Light control

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Supply	Base
Connections - terminals	Bus terminal back)
Movement detection area	4 m 140° 4.43 ft (1.35 m) 5 m of radius (wall) 110° 4.43 ft (1.35 m) 6 m 60° 4.43 ft (1.35 m)
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers EcoStruxure Building Operation SmartX Living Space Sensor base unit

Ordering and shipping details

Category	US1BMS180230
Discount Schedule	BMS1
GTIN	3606489507329
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.7 in (14.4 cm)
Package 1 Width	3.9 in (9.8 cm)
Package 1 Length	2.0 in (5 cm)
Package weight(Lbs)	4.9 oz (140 g)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**3 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**E29cd56a-1ac5-4d02-9266-937a562619e2**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Recyclability potential, in %	**3**
Circularity Profile	**End of Life Information**
Take-back	**No**