Product data sheet

Specifications



communication module Profibus DP V1, Altivar, 12Mbps, 1 female SUB D9 connector

VW3A3607

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Altivar
Product or Component Type	Communication module
Accessory / separate part category	Communication accessories

Complementary

Product Compatibility	Lexium 32M
Range compatibility	Altivar 32 Altivar Machine ATV340 except Sercos drives Altivar Easy 610 Lexium 32 Altivar Process ATV900 Altivar Process ATV600 Altivar Machine ATV320 Altivar Process Modular
Communication Port Protocol	Profibus DP V1
Electrical connection	1 female connector SUB-D 9
Transmission Rate	9.6 kbps...12 Mbps
Addressing	1...126 configurable by graphic terminal/SoMove software Configuration settings
Communication service	4 configurable telegrams Mapping of the process data from the master Parameters management compliant with PROFIdrive V4.1 Several DP V1 messaging modes Drive profile native ATV32 IEC 61800-7-201 (CiA 402)
Display type	1 LED RUN 1 LED bus fault (BF)
diagnostic function	Diagnostic data with VSD status Host drive handled from two masters (MS0 and MS1) Standard identification and maintenance requests
Bus profile	PROFIdrive CiA 402

Environment

Standards	IEC 61800-7-201 (CiA 402)

Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51
GTIN	3606480177583
Returnability	Yes

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.850 in (4.700 cm)
Package 1 Width	2.402 in (6.100 cm)
Package 1 Length	3.543 in (9.000 cm)
Package weight(Lbs)	2.293 oz (65.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	11.8 in (30 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	14.645 lb(US) (6.643 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**104 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**102 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**F26c5dc1-8fcc-4cb7-9720-cb35026be240**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Again

Repack and remanufacture

Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative








VW3A3607
PROFIBUS
6W1004
6W10040120333


Schneider
PROFIBUS

