Product data sheet

Specifications



Wear part, enclosure door, fan for variable speed drive, Altivar Process 600 900, from 0.75 to 5.5kW

VX5VPS1001

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	Altivar Process 600/900
Accessory / Separate Part Type	Fan kit
Accessory / separate part category	Cooling accessory
Product or Component Type	Fan

Complementary

Kit composition	Fan Mounting bracket Instruction sheet
Product compatibility	Variable speed drive ATV630 wall mount 0.75 kW 200...240 V Variable speed drive ATV630 wall mount 1.5 kW 200...240 V Variable speed drive ATV630 wall mount 2.2 kW 200...240 V Variable speed drive ATV630 wall mount 3 kW 200...240 V Variable speed drive ATV630 wall mount 4 kW 200...240 V Variable speed drive ATV630 wall mount 0.75 kW 380...480 V Variable speed drive ATV630 wall mount 1.5 kW 380...480 V Variable speed drive ATV630 wall mount 2.2 kW 380...480 V Variable speed drive ATV630 wall mount 3 kW 380...480 V Variable speed drive ATV630 wall mount 4 kW 380...480 V Variable speed drive ATV630 wall mount 5.5 kW 380...480 V Variable speed drive ATV930 wall mount 0.75 kW 200...240 V Variable speed drive ATV930 wall mount 1.5 kW 200...240 V Variable speed drive ATV930 wall mount 2.2 kW 200...240 V Variable speed drive ATV930 wall mount 3 kW 200...240 V Variable speed drive ATV930 wall mount 4 kW 200...240 V Variable speed drive ATV930 wall mount 0.75 kW 380...480 V Variable speed drive ATV930 wall mount 1.5 kW 380...480 V Variable speed drive ATV930 wall mount 2.2 kW 380...480 V Variable speed drive ATV930 wall mount 3 kW 380...480 V Variable speed drive ATV930 wall mount 4 kW 380...480 V Variable speed drive ATV930 wall mount 5.5 kW 380...480 V

Ordering and shipping details

Category	US1CP4E22276
Discount Schedule	CP4E
GTIN	3606480717376
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.953 in (7.500 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	6.693 in (17.000 cm)
Package 1 Length	9.055 in (23.000 cm)
Package weight(Lbs)	8.677 oz (246.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	5.366 lb(US) (2.434 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Take-back	No