# Product data sheet

Specifications



## Monolithic pilot light, Harmony XB5, grey plastic, red, 22mm, universal LED, plain lens, 24V AC DC

XB5EVB4

**Product availability: Stock - Normally stocked in distribution facility**
**Important message: A change in appearance may be noted on the product but does not affect its use in terms of function and safety. This makes it compatible with our Universal LED blocks**

## Main

| | |
|---|---|
| **Range of Product** | Harmony XB5 |
| **Product or Component Type** | Pilot light |
| **Device short name** | XB5 |
| **Bezel material** | Dark grey plastic |
| **Fixing collar material** | Plastic |
| **Head type** | Standard |
| **Mounting diameter** | 0.9 in (22.5 mm) |
| **Sale per indivisible quantity** | 1 |
| **Shape of signaling unit head** | Round |
| **Cap/operator or lens colour** | Red |
| **Operator additional information** | With plain lens |
| **Light source** | Universal LED |
| **Bulb base** | Integral LED |
| **Light source colour** | Red |
| **[Us] rated supply voltage** | 24 V AC/DC 50/60 Hz |
| **Device presentation** | Monolithic product |

## Complementary

| | |
|---|---|
| **Height** | 1.1 in (29 mm) |
| **Width** | 1.1 in (29 mm) |
| **Depth** | 2.1 in (54 mm) |
| **Terminals description ISO n°1** | (X1-X2)PL |
| **Net Weight** | 0.084 lb(US) (0.038 kg) |
| **Resistance to high pressure washer** | 1015.3 psi (7000000 Pa) 131 °F (55 °C) 0.1 m |
| **Connections - terminals** | Screw clamp terminals, <= 2 x 1.5 mm² with cable end IEC 60947-1<br>Screw clamp terminals, 1 x 0.22...2 x 2.5 mm² without cable end IEC 60947-1 |
| **[Ui] rated insulation voltage** | 250 V 3)IEC 60947-1 |
| **[Uimp] rated impulse withstand voltage** | 4 kV IEC 60947-1 |
| **Signalling type** | Steady |
| **Compatibility code** | XB5 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Supply voltage limits** | 19.2…30 V DC<br>21.6…26.4 V AC |
| **Current Consumption** | 18 mA |
| **Service life** | 100000 h at rated voltage and 25 °C |
| **Surge withstand** | 1 kV IEC 61000-4-5 |

## Environment

| | |
|---|---|
| **Protective treatment** | TH |
| **Ambient Air Temperature for Storage** | -40…158 °F (-40…70 °C) |
| **Ambient Air Temperature for Operation** | -13…158 °F (-25…70 °C) |
| **Overvoltage category** | Class II conforming to IEC 60536 |
| **IP degree of protection** | IP66 IEC 60529<br>IP67 IEC 60529<br>IP69 IEC 60529<br>IP69K ISO 20653 |
| **Enclosure Type** | UL type 4X/13 |
| **IK degree of protection** | IK05 conforming to IEC 50102 |
| **Standards** | IEC 60947-5-1<br>IEC 60947-1<br>UL 508<br>JIS C8201-5-1<br>IEC 60947-5-4<br>CSA C22.2 No 14<br>JIS C8201-1 |
| **Product Certifications** | UL Listed<br>CSA |
| **Vibration resistance** | 5 gn (f= 12…500 Hz) conforming to IEC 60068-2-6 |
| **Shock resistance** | 50 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>30 gn 11 ms) half sine wave acceleration IEC 60068-2-27 |
| **Resistance to fast transients** | 2 kV IEC 61000-4-4 |
| **Resistance to electromagnetic fields** | 9.1 V/m (10 V/m) IEC 61000-4-3 |
| **Electromagnetic compatibility** | Electrostatic discharge - test level: 6 kV (on contact (on metal parts)) conforming to IEC 61000-4-2<br>Electrostatic discharge - test level: 8 kV (in free air (in insulating parts)) conforming to IEC 61000-4-2<br>Electromagnetic emission class B conforming to IEC 55011 |
| **Resistance to electrostatic discharge** | 6 kV on contact (on metal parts) IEC 61000-4-2<br>8 kV in free air (in insulating parts) IEC 61000-4-2 |
| **Electromagnetic emission** | Class B IEC 55011 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS222467 |
| **Discount Schedule** | 0CS2 |
| **GTIN** | 3389119041355 |
| **Returnability** | Yes |
| **Country of origin** | ID |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |

| | |
|---|---|
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 1.339 in (3.400 cm) |
| **Package 1 Width** | 1.378 in (3.500 cm) |
| **Package 1 Length** | 2.362 in (6.000 cm) |
| **Package weight(Lbs)** | 0.811 oz (23.000 g) |
| **Unit Type of Package 2** | S01 |
| **Number of Units in Package 2** | 88 |
| **Package 2 Height** | 5.9 in (15 cm) |
| **Package 2 Width** | 5.9 in (15 cm) |
| **Package 2 Length** | 15.7 in (40 cm) |
| **Package 2 Weight** | 5.196 lb(US) (2.357 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **0.6 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **0.2 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **0 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **0.4 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **0 kg CO2 eq.** |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **Yes** |
| SCIP Number | **3d14fd98-3859-4733-a5ee-a3016769973c** |
| EU RoHS Directive | Compliant By Exemption |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Product repairability index | **A** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **22** |
| Circularity Profile | End of Life Information |
| Take-back | **No** |

Dimensions Drawings

## Dimensions




**e:** clamping thickness: 1 mm to 6 mm / 0.03 in. to 0.24 in.

Image of product / Alternate images

**Alternative**






XB5EVXX





