Product datasheet

Specifications



Low-Voltage Fan Coil Room Controller: Stand Alone, RH sensor & control, Floating or on-off, Hotel/ Lodging

SE7355C5045

To be discontinued

Main

Device application	Low voltage fan coil
Net weight	0.34 kg
Product or component type	Room controller
Product name	SE7000 Series
Device short name	SE7305
Height	124.97 mm
AWG gauge	22 AWG...18 AWG
Directives	89/336/EEC - electromagnetic compatibility
Width	86.87 mm
Market segment	Lodging/hotel
Ambient air temperature for storage	-30…50 °C
Depth	29.97 mm
Ambient air temperature for operation	-0…50 °C
Measurement accuracy	Humidity: +/- 5 %, 20...80 % RH (non-condensing) Temperature: +/- 0.9 °F, (at 70 °F typically calibrated)
Product certifications	CE C-Tick conforming to AS/NZS CISPR 22 FCC conforming to CFR 47 part 15 class A UL listed file E27734 CCN XPAX UL listed file E27734 CCN XPAX7
Information displayed	Temperature: - 40...122 °F
Network frequency	50 Hz 60 Hz
Communication port protocol	Standalone (network ready)
Temperature setting range	4…32 °C heating -17 °C per step 12…38 °C cooling
Humidity setting range	Humidification: 10…90 % Dehumidification: 15…95 %
Calibration certificate	1 pt
Output type	2 xuniversal 1 xdigital
Output voltage	0...10 V DC for universal output 30 V AC for universal output
Input type	1.0 x dry contact

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Output current	1 A relay output 3 A relay output (inrush)
Standards	FCC part 15 Subpart B ICES-003 CSA C22.2 No 24 UL 873
Relative humidity	0…95 % RH, non-condensing
[Us] rated supply voltage	10...30 V AC 50/60 Hz
Sensor type	Single point calibrated bulk polymer RH sensor humidity 10 kOhm T2 NTC thermistor temperature
Range	EcoStruxure Building Expert
Economizer	No
Humidity control	Yes
PIR cover	No
Scheduling	No

Complementary

Device presentation	Without cover
Rated operational power in VA	2 VA
Connections - terminals	Screw terminal
Range compatibility	EcoStruxure Building Expert communication card EcoStruxure Building Expert sensor EcoStruxure Building Expert temperature sensor EcoStruxure Building Expert relay EcoStruxure Building Expert sensor coverplate

Environment

Electrical insulation class	Class II

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.000 cm
Package 1 Width	15.000 cm
Package 1 Length	5.000 cm
Package 1 Weight	200.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.702 kg
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm

Package 3 Length	120.000 cm
Package 3 Weight	55.232 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins