



The Safety Company

1000 Cranberry Woods Drive,
Cranberry Township, PA 16066

MSA Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014
IAC-20-008 - Z04 Rev 0

Statement of Conformity: MSA declares that the
V-SHOCK Overhead Web 6 ft. PFL
is in conformity with the requirements of
OSHA 1910.140, OSHA 1926.502

Table with 2 columns: Product Code, Model / Part Numbers Covered. Row 1: IAC-20-008, VSOW-011-αβ-O, VSOW-011-αβ-O-TB, VSOW-012-αβ-O, VSOW-012-αβ-O-TB. Includes 'Where:' and connector definitions.

ANSI/ISEA 125-2014 conformity assessment method: [X] Level 1 [] Level 2
For Level 2, information about ISO 17025-accredited facility in which the product was tested:
[] The test facility is an independent 3rd Party ISO 17025-accredited facility
[X] The test facility is owned or partially owned by an entity within supplier's corporate structure...
Table with 3 columns: Report, Test Facility Used, Test Facility Document #.

For additional information about this product(s), please contact MSA Customer Service at 1-800-MSA-2222. When requesting information, please reference model number(s).

Brooke Conroy
Brooke Conroy (May 26, 2022 14:21 EDT)

May 26, 2022

QA Rep: Brooke Conroy

Date: MM/DD/YYYY

Performance Details

Revision 0

Report	Standard and Product Requirements	Acceptance Criteria	Pass / Fail
1, 2	Dyanmic Performance Combined Force and Strength Test - Ambient Conditions Force Test OSHA 1910.140 App D (d) OSHA 1926.502(d) App C (d) Strength Test OSHA 1910.140 App D (c) OSHA 1926.502(d) App C (c)	< 2520 lbs. max	PASS
1, 2	Dyanmic Performance Combined Force and Strength Test - Cold Conditions	< 2520 lbs. max	PASS
1, 2	Dyanmic Performance Combined Force and Strength Test - Hot Conditions	< 2520 lbs. max	PASS
1, 2	Dyanmic Performance Combined Force and Strength Test - Wet Conditions	< 2520 lbs. max	PASS
1, 2	Dyanmic Performance Combined Force and Strength Test - Corrosion Conditions	< 2520 lbs. max	PASS
1, 2	Maximum Weight and Maximum Free Fall - Hot Conditions Force Test OSHA 1910.140 App D (d) OSHA 1926.502(d) App C (d)	< 2520 lbs. max	PASS
1, 2	Static Strength - Corrosion Conditions 1910.140(c)(5) 1926.502(d)(12) SRLs that limit free fall to 2 ft.	3600 lb for 300 sec	PASS