

Medium Duty Reinforced WAT

3-way fiberglass reinforced natural kraft carton sealing tape manufactured with water-activated adhesive available in Natural, Snowwhite and Superwhite.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads.

ADHESION

(WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	
2/0	44 mm-kgf
2/1	66 mm-kgf
5/0	70 mm-kgf
15/0	86 mm-kgf
MCLAURIN	
	86



NOMINAL VALUES

The following data are nominal values based on ASTM and other standard tests. This data should not be considered specification.

PHYSICAL PROPERTIES

Caliper	7 mils (0.2 mm)
MD Tensile ASTM 33650	83 lb (363.4 N/25mm)
CD Tensile ASTM 33650	30 lb (131.3 N/25mm)

Recommended for use on average weight cartons up to 55 pounds (25 kg).

CONSTRUCTION PER SQUARE

TOP PLY ASTM 33650	25 lb (41 g/m2) Kraft Paper virgin fibers
BOTTOM PLY ASTM 33650	25 lb (41 g/m2) Kraft Paper virgin fibers
LAMINATING ADHESIVE	High Melt Index Polypropylene Based Co-Polymer
WATER-ACTIVATED ADHESIVE	Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911
MD REINFORCEMENT	(2-1-1-1-2) 75 Fiberglass (per 3"), ½" spacing
CD REINFORCEMENT	(1-1-1) 150 Fiberglass, 1.10" spacing, 43 degree angle

CUSTOMER SERVICE: 800.474.8273
TAPE TECHNICAL SERVICE: 877.447.4832
INSIDE SALES: 888.898.7834 | INFO@ITAPE.COM

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.