

## Heavy Duty Reinforced WAT

3-way fiberglass reinforced, strippable carton sealing tape manufactured with water-activated adhesive available in Natural and Snowwhite.

### PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on average to heavyweight cartons up to 65 lbs/30 kg.

### ADHESION

(WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	
2/0	38 mm-kgf
2/1	58 mm-kgf
5/0	69 mm-kgf
15/0	87 mm-kgf
MCLAURIN	
	86



### NOMINAL VALUES

The following data are nominal values based on ASTM and other standard tests. This data should not be considered specification.

### PHYSICAL PROPERTIES

Caliper	7.5 mils (0.2 mm)
---------	-------------------

### CONSTRUCTION PER SQUARE

<b>TOP PLY</b> ASTM 33650	25 lb (41 g/m <sup>2</sup> ) Kraft Paper virgin fibers
<b>BOTTOM PLY</b> ASTM 33650	30 lb (49 g/m <sup>2</sup> ) Kraft Paper virgin fibers
<b>LAMINATING ADHESIVE</b>	High Melt Index Polypropylene Based Co-Polymer
<b>WATER-ACTIVATED ADHESIVE</b>	Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911
<b>MD REINFORCEMENT</b>	(2-1-1-1-2) 110 Fiberglass (per 3"), ½" spacing
<b>CD REINFORCEMENT</b>	(1-1-1), 150 Fiberglass, 0.55" spacing, 43 degree angle

CUSTOMER SERVICE: 800.474.8273  
TAPE TECHNICAL SERVICE: 877.447.4832  
INSIDE SALES: 888.898.7834 | INFO@ITAPE.COM

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.