



The Safety Company

1000 Cranberry Woods Drive,
Cranberry Township, PA 16066

MSA Declaration of Conformity

In Accordance with ANSI/ASSP Z359.7-2019
IAC-23-069 - Z04 Rev 4

Statement of Conformity: MSA declares that the
V-SERIES RESTRAINT LANYARDS
is in conformity with the requirements of
ANSI/ASSP Z359.3-2019

Table with 2 columns: Product Code, Model / Part Numbers Covered. Row 1: IAC-23-069, L/R/1/F/NT, L/R/1/A/NT, ME/R/1/F/TB, ME/R/1/A/TB, CB/R/1/F/NT-ANSI, XT/D/1, XT/D/2

ANSI/ISEA 125-2014 conformity assessment method: [] Level 1 [X] Level 2
For Level 2, information about ISO 17025-accredited facility in which the product was tested:
[] The test facility is an independent 3rd Party ISO 17025-accredited facility
ISO Accrediting Agency:
[X] The test facility is owned or partially owned by an entity within supplier's corporate structure,
or within the manufacturing stream for this product, including subcontractors and sub-
suppliers.
ISO Accrediting Agency: ANAB ANSI National Accreditation Board
Report: 1 Test Facility Used: FPLab Test Facility Document #: FPLAB-164-05

For additional information about this product(s), please contact MSA Customer Service at 1-800-MSA-2222. When requesting information, please reference model number(s).

Vinny Iachini
Compliance Engineer: Vinny Iachini

02/18/2025
Date: MM/DD/YYYY

Mitch Hetrich
Qualified Person: Mitch Hetrich

02/21/2025
Date: MM/DD/YYYY

Performance Details

Revision 4

| Report | Standard and Product Requirements | Acceptance Criteria | Pass / Fail |
|---------------|--|--|--------------------|
| 1 | 4.2.1 (3.4.1) Lanyard Static Strength Test - Load sample to at least 5000 lbf (22kN) for a period no less than one minute. | Lanyards shall have a breaking strength no less than 5000 lbf (22kN) | Pass |
| 1 | 4.2.2 (3.4.2) Adjustable Lanyards Static Strength and Slip Test - Load sample to 1000 lbf (4.4kN) for at least one minute. Note any slip through adjusters. Continue loading to 5000 lbf (22kN) for at least one minute. | Lanyards shall maintain their adjusted length within 3 inches when loaded to 1000 lbf (4.4kN), and shall have a breaking strength no less than 5000 lbf (22kN) | Pass |
| 1 | 4.2.4 (3.4.3 / 3.5.3) Lanyard Dynamic Strength Test - Drop 282lb (128kg) test mass from a height necessary to apply a peak impact load of not less than 3,600 lbf (16kN), or a maximum distance of 4 feet (1.2m), whichever is less. | Lanyards and adjustable lanyards shall not break and shall retain the weight for a period no less than one minute | Pass |

| Revision | Date | Project Engineer | Qualified Person |
|-----------------|-------------|-------------------------|-------------------------|
| 0 | 1/11/2019 | Loryn Bertoti | Loryn Bertoti |
| 1 | 9/19/2019 | Loryn Bertoti | Loryn Bertoti |
| 2 | 10/8/2020 | Loryn Bertoti | Loryn Bertoti |
| 3 | 10/29/2024 | Mitch Hetrich | Mitch Hetrich |
| 4 | 2/18/2025 | Mitch Hetrich | Mitch Hetrich |