



The Safety Company

1000 Cranberry Woods Drive,
Cranberry Township, PA 16066

MSA Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014

IAC-03-006 - Z04 Rev 10

Statement of Conformity: MSA declares that the
V-Gard® Mesh Visors for General Purpose
is in conformity with the requirements of
ANSI/ISEA Z87.1-2020

Table with 2 columns: Product Code, Model / Part Numbers Covered. Contains product code IAC-03-006 and a list of model numbers and a detailed description of the visor part numbers meeting ANSI/ISEA Z87.1-2020 requirements.

ANSI/ISEA 125-2014 conformity assessment method: [] Level 1 [X] Level 2
For Level 2, information about ISO 17025-accredited facility in which the product was tested:
[X] The test facility is an independent 3rd Party
[] The test facility is owned or partially owned by an entity within supplier's corporate structure...
Table with 3 columns: Report, Test Facility Used, Test Facility Document #

For additional information about this product(s), please contact MSA Customer Service at 1-800-MSA-2222. When requesting information, please reference model number(s).

Brooke Conroy

Jul 20, 2023

Quality Assurance: B. Conroy

Date:

Performance Details

Revision 10

Report	Standard and Product Requirements	Results	Pass / Fail
1	5.2.1 (9.6) - Drop Ball Impact Resistance: Protector shall fail if any of the following occur when impacted by a 25.4mm (1 in.) diameter steel ball when dropped from a height of 127 cm (50 in.): - lens (lens only) fractures - piece fully detached from the inner surface - projectile penetrates the inner surface - lens not retained	No fracture, detachment, etc.	Pass
1	5.2.2 (9.7) - Ignition: Protectors shall not ignite or continue to glow once the heated rod is removed.	No ignition or afterglow	Pass
2, 3	5.2.1 (9.6) - Drop Ball Impact Resistance: Protector shall fail if any of the following occur when impacted by a 25.4mm (1 in.) diameter steel ball when dropped from a height of 127 cm (50 in.): - lens (lens only) fractures - piece fully detached from the inner surface - projectile penetrates the inner surface - lens not retained	No fracture, detachment, etc.	Pass
3	7.1.3 (9.10) - Lateral (Side) Coverage: Impact-rated protectors shall provide continuous lateral coverage (i.e. no openings greater than 1.5 mm in diameter) from the edge of the lens to a point not less than 10 mm posterior to the corneal plane and not less than 10 mm above or below the horizontal plane centered on the eyes of the headform.	Continuous coverage	Pass