



BOSCH

PROFACTOR™

CONCRETE TO THE CORE

SDS-max® impact in a powerful 18V hammer

HITMAN™

POWERED BY CORE18V

GBH18V-45C

#BOSCHPROFACTOR
#BOSCHCORE18V
#BOSCHHITMAN



9.3
ft.-lbs

SUPERIOR IMPACT

Delivers 9.3 Ft.-Lbs. of impact energy (EPTA) for full performance in concrete when drilling and chiseling



BITURBO BRUSHLESS™ TECHNOLOGY

Featuring a brushless high-performance motor and drive-train system engineered to take full advantage of the additional power generated by CORE18V PROFACTOR™ batteries

CORE18V™
8.0 Ah 12.0 Ah



KICKBACK CONTROL TECHNOLOGY

Reduces the risk of sudden tool reactions in binding conditions



ANTI-VIBRATION SYSTEM

Helps reduce vibration with a longer air cushion in the hammer tube, dampeners in the handle and a counter-balance weight in the hammer mechanism

BEST-IN-CLASS CORDLESS PERFORMANCE WITH 9.3 FT.-LBS. of impact energy

OPTIMAL FOR (TRADES)



LEARN MORE
www.boschtools.com

PROFACTOR™ HIGH-POWERED CORDLESS SYSTEM



BITURBO
BRUSHLESS.



CORE18V™
8.0 Ah 12.0 Ah



HELL-ION™
(OPTIONAL)

18V HITMAN™ CONNECTED-READY SDS-max® 1-7/8" ROTARY HAMMER

GBH18V-45C



KICKBACK CONTROL TECHNOLOGY

Reduces the risk of sudden tool reactions in binding conditions



VARIO-LOCK POSITIONING

Rotates and locks chisel to optimize working angle



BITURBO BRUSHLESS™ TECHNOLOGY

Featuring a brushless high-performance motor and drive-train system engineered to take full advantage of the additional power generated by CORE18V PROFACOR™ batteries



CORE18V™
8.0 Ah / 12.0 Ah

SELECTOR SWITCH

Selects between drilling, Vario-Lock and hammering modes



ANTI-VIBRATION SYSTEM

Helps reduce vibration with a longer air cushion in the hammer tube, dampeners in the handle and a counter-balance weight in the hammer mechanism



LOCK-ON / LOCK-OFF BUTTON

Keeps tool running when locked on (hammer-mode only) and helps prevent accidental activation of the trigger when locked off

USER INTERFACE

On-tool display helps manage tool performance for immediate feedback and control

CONNECTIVITY (MODULE SOLD SEPARATELY)

Link to connected device via Bosch Toolbox App to customize settings and receive detailed feedback



LED WORKLIGHT

Illuminates dark work areas

Specifications

| | |
|----------------------|-----------------|
| Voltage | 18V |
| Hammer Size | 1-7/8" SDS-max® |
| Impact Energy (EPTA) | 9.3 ft.-lbs. |
| RPM / BPM | 0-305 / 0-2,760 |
| Length | 21.5" |
| Weight (Bare Tool) | 17.6 lbs. |

Includes

| | |
|---------------|--|
| GBH18V-45CK | GBH18V-45C PROFACOR™ 18V Hitman™ Connected-Ready SDS-max® 1-7/8 In. Rotary Hammer, Auxiliary Handle, Carrying Case |
| GBH18V-45CK24 | GBH18V-45C PROFACOR™ 18V Hitman™ Connected-Ready SDS-max® 1-7/8 In. Rotary Hammer, GBA18V80 (2) 18V CORE18V Lithium-ion 8.0 Ah PROFACOR™ Performance Batteries, GAL18V-160C 18V Connected-Ready 16 Amp Battery Turbo Charger, Auxiliary Handle, Carrying Case |
| GBH18V-45CK27 | GBH18V-45C PROFACOR™ 18V Hitman™ Connected-Ready SDS-max® 1-7/8 In. Rotary Hammer, GBA18V120 (2) 18V CORE18V Lithium-ion 12.0 Ah PROFACOR™ Exclusive Batteries, GAL18V-160C 18V Hell-ion Connected-Ready Lithium-ion 16 Amp Battery Turbo Charger, Auxiliary Handle, Carrying Case |



BOSCH

PROVANTAGE
TOOL & BATTERY PROTECTION PLAN

| | | |
|---------------------------|--------------------|----------------------|
| 3 YEARS TOOL & CHARGER | 2 YEARS BATTERY | 180 DAY GUARANTEE |
|---------------------------|--------------------|----------------------|

Robert Bosch Tool Corporation
1800 W. Central Rd.
Mount Prospect, IL 60056
www.boschtools.com

2021-008