



BOSCH

SEE THE TEMP

In High Definition

GTC600C



HIGH-RESOLUTION DISPLAY

Provides sharp, detailed thermal images with option to store up to 500 pictures



BUILT-IN MIC/SPEAKER AND VOICE NOTE FEATURE

For fast and easy documentation



BROAD MEASURING RANGE OF -4 °F - 1112 °F (-20 °C - +600 °C)

For accurate usage in a wide range of applications



INTEGRATED CONNECTIVITY

Easily connect via Wi-Fi to use the Bosch Thermal Connect App or GTC Transfer to analyze and document images, as well as create full reports

HIGH-RESOLUTION DISPLAY

for more detailed thermal images

OPTIMAL FOR



CONCRETE SPECIALIST



MECHANICAL



INTERIOR FINISH



MRO

LEARN MORE
www.boschtools.com

**12V
MAX**

EXCHANGABLE, LONG-LASTING POWER

SCAN HERE FOR
MORE BOSCH TOOLS



12V MAX CONNECTED THERMAL CAMERA

GTC600C

**12V
MAX**

INTEGRATED CONNECTIVITY

Enables seamless storing, transferring, and analyzing of images using the Bosch Connect App or GTC Transfer when connected to Wi-Fi



BROAD MEASURING RANGE

-4 °F - 1112 °F (-20 °C - +600 °C) range provides accurate usage in a wide range of applications



BUILT-IN MIC/SPEAKER

Allows for fast and easy documentation of measurements using the voice note feature



THERMAL IMAGE TRIGGER

Easy-to-use trigger system to detect and document temperature measurements

FOCUS ON DOCUMENTATION

Offers quick orientation inside the device with enhanced gallery features and categorized emissivity values



HIGH RESOLUTION DISPLAY

Provides sharp, detailed thermal images



JOBSITE TOUGH CONSTRUCTION

Reinforced rubber housing offers impact resistance and IP54 rating helps protect from rainy and dusty conditions

INTUITIVE USER INTERFACE

Intuitive handling delivers successful results with minimal clicks for beginners or pros



ERGONOMIC DESIGN

Promotes better grip, comfort and control for increased productivity



BOSCH 12V BATTERY SYSTEM

Exchangeable, long-lasting power

Specifications	
Resolution Infrared Sensor	256 x 192 pixels
Measuring Range	-4 °F... 1112 °F (-20 °C ... +600 °C)
Measuring Accuracy of IR	2°C or 2%
Thermal Sensitivity (NETD)	≤ 50
Dust and Splash Water Protection	IP54
Weight (Bare Tool / w/ Battery)	1.41lbs (0,64 kg)

Includes	
GTC600C	(1) GTC600C 12V Max Connected Thermal Camera, (1) BAT414 12V Max Lithium-Ion 2.0 Ah, (1) GAL12V-20 12V Max Lithium-Ion Battery Charger, (1) USB-A to USB-C Cable, (1) Plastic Case



BOSCH

LIMITED WARRANTY

1 YEAR* Tool
1 YEAR Battery/Charger

*Register your tool within (8) weeks of purchase for a total of two (2) years coverage. For full terms, visit <https://rb-pt.io/PowerToolWarranty> or call 1-877-BOSCH99

Robert Bosch Tool Corporation
1800 W. Central Rd.
Mount Prospect, IL 60056
www.boschtools.com

2023-330