



SPRING CLAMPS

When you need to apply clamping pressure quickly and easily Palmgren's spring clamps deliver proven durability and strong clamping pressure. Throughout the clamps range of opening the point of clamping pressure always remains at the jaw tips to ensure they'll hold together exactly where you need them too. Applications for these universal clamps are unlimited and they can be used on metal, wood, plastic, fabric as well as any additional materials that need to be held in place.

- Manufactured 100% in the USA
- Up to 30% more clamping pressure than the imports
- Tang compression spring keeps the jaws in alignment
- Available with or without poly-vinyl protective tips
- Will hold down materials for both indoor and outdoor tasks



Item #	Description	Overall Length	Overall Height	Overall Width	Jaw Opening Max	Throat Depth	Jaw Width	Clamping Pressure	Weight
64011	1" Spring Clamps with Tips	4"	2.5"	0.835"	1.089"	1.29"	0.835"	95 lbs.	0.15 lbs.
64012	2" Spring Clamps with Tips	6.50"	3.75"	1.130"	1.930"	2.2"	1.130"	80 lbs.	0.40 lbs.
64013	3" Spring Clamps with Tips	9.5"	6.5"	1.405"	3.425"	3.085"	1.405"	75 lbs.	0.95 lbs.
64014	4" Spring Clamps with Tips	12.375"	8.5"	1.405"	4.865"	4.065"	1.405"	75 lbs.	1.25 lbs.
64021	1" Spring Clamps without Tips	4"	2.5"	0.835"	1.089"	1.29"	0.835"	95 lbs.	0.13 lbs.
64022	2" Spring Clamps without Tips	6.50"	3.75"	1.130"	1.930"	2.2"	1.130"	80 lbs.	0.35 lbs.
64023	3" Spring Clamps without Tips	9.5"	6.5"	1.405"	3.425"	3.085"	1.405"	75 lbs.	0.90 lbs.
64024	4" Spring Clamps without Tips	12.375"	8.5"	1.405"	4.865"	4.065"	1.405"	75 lbs.	1.18 lbs.