

REGULAR DUTY DROP FORGED C-CLAMPS

Palmgren's high tech line of drop forged C-clamps delivers performance and features in a C-clamp that count. Built from state of the art research and computer aided design, these clamps provide higher strength, lower weight, coupled with advanced heat treating on both the body and spindle creates C-clamps that hold securely and safely up to their rated maximum capacities. Palmgren's dropped forged clamps are cost effective, versatile, durable and long lasting.

- High strength dropped forged frame
- Spindles are full length, machined from a single piece of tempered and hardened steel
- Square spindle heads stand up to wrench tightening
- Black-oxide plated spindles resist wear while impeding rust
- Replaceable swivel pads
- Frames complete with lacquer finish
- Lifetime warranty against breakage

Item #	Opening	Throat Depth	Spindle Diameter	Clamp Pressure	Weight
9629097	0-4"	2-1/8"	5/8"	6200 lbs.	2.4 lbs.
9629098	0-6"	2-7/8"	13/16"	6900 lbs.	6.4 lbs.
9629099	0-8"	3-7/8"	15/16"	6900 lbs.	8.7 lbs.
9629105	0-10"	4-7/8"	15/16"	8000 lbs.	12.1 lbs.
9629106	0-12"	5"	1-1/8"	9300 lbs.	18.3 lbs.



REGULAR DUTY DROP FORGED COPPER SPINDLE C-CLAMPS

Palmgren's high tech line of drop forged C-clamps delivers performance and features in a C-clamp that count. Built from state of the art research and computer aided design, these clamps provide higher strength, lower weight, coupled with advanced heat treating on both the body and spindle creates C-clamps that hold securely and safely up to their rated maximum capacities. Palmgren's dropped forged clamps are cost effective, versatile, durable and long lasting.

- High strength dropped forged frame
- Spindles are full length, machined from a single piece of tempered and hardened steel
- Square spindle heads stand up to wrench tightening
- Copper plated anti-welding splatter spindles
- Replaceable swivel pads
- Frames complete with lacquer finish
- Lifetime warranty against breakage

Item #	Opening	Throat Depth	Spindle Diameter	Clamp Pressure	Weight
9629107	0-4"	2-1/8"	5/8"	6200 lbs.	2.4 lbs.
9629108	0-6"	2-7/8"	13/16"	6900 lbs.	6.4 lbs.
9629109	0-8"	3-7/8"	15/16"	6900 lbs.	8.7 lbs.
9629110	0-10"	4-7/8"	15/16"	8000 lbs.	12.1 lbs.
9629111	0-12"	5"	1-1/8"	9300 lbs.	18.3 lbs.

