

REGULAR DUTY DROP FORGED DEEP THROAT C-CLAMPS

Palmgren's line of drop forged C-clamps delivers performance and features in a C-clamp that count. These clamps provide higher strength, lower weight, coupled with advanced heat treating on both the body and spindle. This creates a C-clamp that holds securely and safely up to the rated maximum capacity. Palmgren's dropped forged clamps are cost effective, versatile, durable, and long lasting.

- High strength dropped forged frame
- Spindles are full length, machined from a single piece of tempered and hardened steel
- Black-oxide plated spindles resist wear while impeding rust
- Replaceable swivel pads
- Frames complete with lacquer finish
- Lifetime warranty against breakage

Item #	Opening	Throat Depth	Max Clamping Force	Spindle Diameter	Spindle Hex Size	Weight
9629510	0 - 2"	2-1/8"	3,960 lbs.	0.405"	9/16"	1.4 lbs.
9629511	0 - 3"	2-1/2"	4,400 lbs.	0.527"	3/4"	2 lbs.
9629512	0 - 4"	3-1/4"	6,600 lbs.	0.670"	7/8"	3.3 lbs.
9629513	0 - 6"	4-1/8"	8,800 lbs.	0.670"	7/8"	5.1 lbs.
9629514	0 - 8"	5"	8,800 lbs.	0.670"	7/8"	8.1 lbs.
9629515	0 - 10"	6"	8,800 lbs.	0.670"	7/8"	11 lbs.
9629516	0 - 12"	6-3/10"	8,800 lbs.	0.670"	7/8"	13.9 lbs.



REGULAR DUTY DROP FORGED DEEP THROAT COPPER SPINDLE C-CLAMPS

Palmgren's line of drop forged C-clamps delivers performance and features in a C-clamp that count. These clamps provide higher strength, lower weight, coupled with advanced heat treating on both the body and spindle. This creates a C-clamp that holds securely and safely up to the rated maximum capacity. Palmgren's dropped forged clamps are cost effective, versatile, durable, and long lasting.

- High strength dropped forged frame
- Spindles are full length, machined from a single piece of tempered and hardened steel
- Copper plated anti-welding splatter spindles
- Replaceable swivel pads
- Frames complete with lacquer finish
- Lifetime warranty against breakage

Item #	Opening	Throat Depth	Max Clamping Force	Spindle Diameter	Spindle Hex Size	Weight
9629517	0 - 2"	2-1/8"	3,960 lbs.	0.405"	9/16"	1.4 lbs.
9629518	0 - 3"	2-1/2"	4,400 lbs.	0.527"	3/4"	2 lbs.
9629519	0 - 4"	3-1/4"	6,600 lbs.	0.670"	7/8"	3.3 lbs.
9629520	0 - 6"	4-1/8"	8,800 lbs.	0.670"	7/8"	5.1 lbs.
9629521	0 - 8"	5"	8,800 lbs.	0.670"	7/8"	8.1 lbs.
9629522	0 - 10"	6"	8,800 lbs.	0.670"	7/8"	11 lbs.
9629523	0 - 12"	6-3/10"	8,800 lbs.	0.670"	7/8"	13.9 lbs.

