

# 360-DEGREE PROTECTION ON UNEVEN TERRAIN

Fully enclosed platform keeps you stable, level, and protected while working at height on rough, uneven jobsites.



### ONE SETUP. MULTIPLE HEIGHTS

Patented Rapid Locks<sup>™</sup> let you raise or lower the platform height in seconds.



### WORK LEVEL ON UNEVEN GROUND

Legs adjust independently to match the terrain.



### KNOW WHEN TO STEP OFF

Patented Ground Cue<sup>®</sup> gives a distinct click you can hear and feel when you hit the bottom rung.

## SERIOUS SIDE-TIP STABILITY

All-terrain legs expand the base for unmatched side-tip protection.



# HOLD YOUR GROUND. RULE THE JOBSITE.

The Adjustable Fortress All-Terrain gives you 360-degree protection and pro-grade performance without compromise.



SCAN TO SEE IT IN ACTION!



## FULL CIRCLE SAFETY

The Adjustable Fortress™ gives you 360-degree freedom to work all around the platform. Enclosed rails, wraparound protection, and an auto-closing gate keep you secure from every angle—so you can move, reach, and get it done without compromise.

## ONE SETUP. MULTIPLE HEIGHTS.

Patented Rapid Locks™ let you raise or lower the rails in seconds giving you fast, secure height adjustment that keeps pace with the job.

## WORK SAFER WITH ALL-TERRAIN STABILITY

All-terrain outriggers expand the base for unmatched side-tip protection. Each leg adjusts independently, keeping you level and secure on gravel, slopes, or uneven ground.

## KNOW WHEN TO STEP OFF

The patented Ground Cue® gives a distinct click you can hear and feel, so you know when you've hit the bottom rung. No second-guessing. No rolled ankles. Just confidence with every step.

## FAST SETUP. EASY STORAGE.

Set up in one smooth motion—just push to open, pull to fold. The wheel kit makes adjusting the rails quick and effortless, so you're ready to work in seconds. When the job's done, it folds flat for slim, space-saving storage.

## ROLL WITHOUT THE STRAIN

Tip & Glide™ wheels take the weight off, speeding up transport and cutting down fatigue. Your energy belongs on the job, not getting there.



**NON-CONDUCTIVE  
FIBERGLASS**



**TYPE IAA  
SUPER DUTY**



| Part # | Model | Material   | Weight* | Highest Standing Level | Max Reach** | Storage Width at Base | Duty Rating         |
|--------|-------|------------|---------|------------------------|-------------|-----------------------|---------------------|
| 19324  | 3'    | Fiberglass | 75 lbs  | 7' 4"                  | 31' 10"     | 2' 7"                 | Type IAA (375 lbs.) |

\*Listed weights are approximate and may vary slightly due to manufacturing tolerances

\*\*A 5' 6" person with a 12" vertical reach