

KIMTECH™

Kimtech™ Sterling™ Nitrile Gloves



Textured fingertips
for enhanced grip

Protection of nitrile
with the sensitivity of latex

Beaded cuffs
for easier donning

Kimtech™ Sterling™ Nitrile Gloves guard against contamination by chemical splash and micro-organism hazards, delivering seamless protection when and where it counts. The powder-free gloves are ideal for use in research and production facilities for forensics, life sciences and non-sterile drug manufacturing applications.

The gloves feature an innovative approach to using synthetic nitrile polymer resulting in static dissipative in-use gloves with a tip thickness of just 0.09mm, but with excellent tensile strength suitable for rigorous process use.

These patented physical properties offer all of the

comfort and ease of latex but with the enhanced chemical and mechanical protection of nitrile, along with a reduced potential for TYPE 1 glove-associated allergic reactions.

Precision manufacturing reduces the risk of contamination and ensures the nitrile gloves offer high levels of regulatory compliance. Beaded cuffs and textured fingertips enable excellent handling of both wet and dry materials, and the ambidextrous gloves have been extensively tested under stringent conditions. In addition, the thin nitrile construction and efficient packaging mean that the chemical-resistant gloves can reduce waste by up to 33%.

WWW.ANSELL.COM

Ansell

Kimtech™ Sterling™ Nitrile Gloves

Textured fingertips


Excellent tactile sensitivity



Latex-free

Beaded cuff

Size Guide

SIZE	CODE	LENGTH	QUANTITY 10x per case
XS	99210	24cm	 150x per box = 1,500
S	99211	24cm	
M	99212	24cm	
L	99213	25cm	140x per box = 1,400
XL	99214	25cm	

Product Specifications

CHARACTERISTIC	VALUE					TEST METHODS
- Freedom from holes	AQL 0.65					EN 374-2 and ASTM D 5151
TENSILE PROPERTIES	TENSILE STRENGTH		ULTIMATE ELONGATION			ASTM D 412, ASTM D 573 and ASTM D 3578
- Before aging	42 MPa, nominal		650% nominal			
- After accelerated aging	38 MPa, nominal		550% nominal			
DIMENSION	NOMINAL THICKNESS/WIDTH					ASTM D 3767, ASTM D 6319 and EN 21420
Thickness (mm)	Middle finger		Palm	Cuff		
	0.09		0.08	0.06		
Palm width (mm)	X-Small 70	Small 80	Medium 95	Large 110	X-Large 115	ASTM D 3767, ASTM D 6319 and EN 21420

Key Features

- › Manufactured using proprietary Sterling™ technology that combines security and comfort. The efficient, environmentally-friendly construction minimises waste without compromising safety
- › Nitrile construction results in products that are stronger and leaner than latex gloves, and feature certified protection against a wide range of contaminants while also being food contact approved
- › Gloves are anti-static tested to protect the wearer and equipment
- › Textured fingertips enhance grip and tactile sensitivity for safer and more efficient processes
- › Beaded cuffs add strength to the gloves, reducing the risk of tearing and increasing their durability, while also reducing roll down for easier donning and doffing
- › Contain no natural rubber latex, silicone or powder, reducing the risks of skin irritation for the wearer
- › Ambidextrous and grey in colour

Assured Compliance

- › PPE Cat III according to Regulation (EU) 2016/425 and to the Regulation 2016/425 as brought into the UK law and amended
- › EN ISO 374-1 Type C (K) Chemical Splash protection
- › EN 374-4 Resistance to degradation by chemicals
- › EN ISO 374-5 Micro Organism and VIRUS Protection
- › Food contact approved

Quality Standards

- › Manufactured in accordance with ISO 9001 and ISO 13485
- › Manufactured in compliance with FDA CFR 21 part 820



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
T: +603 8310 6688
F: +603 8310 6699

UK

Ansell Nitritex
T: +44 1638 663338
F: +44 1638 668890

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

The colour Gray and Sterling™ are trademarks of Owens & Minor, Inc. or its affiliates and used under license.

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending.
www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.