

# Central® Brand Natural Paper Tapes

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### DESCRIPTION

Kraft carton sealing tape manufactured with water-activated adhesive. Repulpable.

PROPERTIES	140 LIGHT DUTY	160 MEDIUM DUTY	190 HEAVY DUTY	160 GREEN CORE®
<b>Adhesive</b>	Starch Based Adhesive	Starch Based Adhesive	Starch Based Adhesive	S3911 Starch Based Adhesive
<b>Caliper</b> (mils)	4.3 (0.11mm)	5.6 (0.14mm)	8.0 (0.20mm)	6.1 (0.15mm)
<b>MD Tensile</b> (lbs/in)	30 (131 N/25mm)	45 (197 N/25mm)	65 (285 N/25mm)	44 (193 N/25mm)
<b>CD Tensile</b> (lbs/in)	15 (66 N/25mm)	23 (101 N/25mm)	28 (123 N/25mm)	20 (88 N/25mm)
<b>Adhesion</b> (water at recommended 110°F/43°C)				
Fipago 2/0	20	23	20	48
Fipago 2/1	40	42	40	68
Fipago 5/0	46	48	46	70
Fipago 15/0	84	82	84	87
McLaurin	33	34	33	89
<b>Core</b>	Yes	Yes	Yes	Yes
<b>Standard Wind</b>	GSO	GSI	GSI	GSI
<b>Application</b>	For inner carton sealing or deli and butcher wrap.	For inner carton sealing or for lightweight cartons shipped in unitized loads or full pallets.	For medium weight or standard size cartons shipped in unitized loads or full pallets.	For inner carton sealing or for lightweight cartons shipped in unitized loads or full pallets. Contains 50% recycled fibers.

### STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

### SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to two years from date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within 6 months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
 Customer Service: 800.IPG.8273 | 800.474.8273  
 Tape Technical Service: 877.447.4832  
 www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and

EFFECTIVE: 03/25



# Central® Brand White Paper Tapes

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### DESCRIPTION

Bleached kraft carton sealing tape manufactured with water-activated adhesive. Repulpable.

PROPERTIES	140 LIGHT DUTY	160 MEDIUM DUTY	190 HEAVY DUTY
<b>Adhesive</b>	Starch Based Adhesive	Starch Based Adhesive	Starch Based Adhesive
<b>Caliper</b> (mils)	5.2 (0.13mm)	5.2 (0.13mm)	7.8 (0.20mm)
<b>MD Tensile</b> (lbs/in)	48 (213 N/25mm)	57 (250 N/25mm)	68 (298 N/25mm)
<b>CD Tensile</b> (lbs/in)	23 (102 N/25mm)	26 (114 N/25mm)	28 (123 N/25mm)
<b>Adhesion</b> (water at recommended 110°F/43°C)			
Fipago 2/0	20	20	20
Fipago 2/1	40	40	40
Fipago 5/0	46	46	46
Fipago 15/0	84	84	84
McLaurin	33	33	33
<b>Core</b>	Yes	Yes	Yes
<b>Standard Wind</b>	GSO	GSI	GSI
<b>Application</b>	For inner carton sealing or deli and butcher wrap.	For inner carton sealing or for lightweight cartons shipped in unitized loads or full pallets.	For medium weight or standard size cartons shipped in unitized loads or full pallets.

### STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

### SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to two years from date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within 6 months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
 Customer Service: 800.IPG.8273 | 800.474.8273  
 Tape Technical Service: 877.447.4832  
 www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and

EFFECTIVE: 03/25

